#### MAHARASHTRA POLLUTION CONTROL BOARD

Phone

4010437/4020781

/4037124/4035273 24044532/4024068 /4023516

Email

enquiry@mpcb.gov.in

Visit At : http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near

Sion Circle, Sion (E),

Mumbai - 400 022

Consent order No: BO/JD(APC)/EIC No. PN-19761-13/O/CC- \5\5 Date- 15/2/2014.

M/s. Emerson Climate Technologies (I) Ltd.(Ancillary Unit)

A/P Harpalwadi

Tal. & Dist. Satara

Maharashtra.

Subject: Renewal of Consent to Operate RED category.

Ref

: 1. Earlier Consent granted vide no. BO/JD(APC)/EIC No. PN-17725

13/O/CC-7683 dtd. 13/09/2013.

2. Minutes of CC meeting held on 12.02.2014.

Your application For Renewal of Consent to operate.

Dated: 24/10/2013.

Under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & TM) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- The consent is granted for a period from 01/01/2014 to 30/11/2016
- 2. The actual capital investment of the industry is Rs. 46.29 Crores. (As per C.A. Certificate submitted by industry)
- The Consent is valid for the manufacture of -

Sr: No:	Product I By- Product Name	Maximum Quantity	UOM*
1.	Cylinder Head	5,28,000	Nos./Year
2.	Piston	3,96,000	Sets/Year
3.	Stator	18,00,000	Nos./Year
4.	Rotor	18,00,000	Nos./Year
5.	Bearings	5,28,000	Nos./Year
6.	Body (Crank Case)	16,50,000	Nos./Year
7.	Connecting Rod	1,98,000	Sets/Year
8.	Shaft	16,50,000	Nos./Year
			( 1 Set = 2 Nos.)

SRO Satara/R/L/52493000

# 4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. no.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
1.	Trade effluent	32.5	As per Schedule –I	Recycle and On land
2.	Domestic effluent	44.0	As per Schedule –I	Recycle and On land

## 5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr. no.	Description of stack / source	Number of Stack	Standards to be achieved
1.	Boiler (Thermopack)	01 No.	As per Schedule -II
2.	Decarb Furnace	02 Nos.	As per Schedule -II
3.	Varnish Oven	01 No.	As per Schedule -II
4.	Stack Welding	01 No.	
5.	DG Set (750 KVA)	02 Nos.	As per Schedule -II
6.	DG Set ( 110 KVA)	01 No.	As per Schedule -II

# 6. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

	Type Of Waste	<b>.y</b>	- Quantit y	UOM	Treatme nt	Disposal
1	Used /Spent Oil	5.1	15.0	KL/A	-	Sale to MPCB authorized recycler
2	Waste Residue containing oil (Cotton Waste)	5.2	15.0	MT/A	-	CHWTSDF
3	Flue gas dust & other particulate	11.4	0.5	MT/A	-	CHWTSDF
4	Waste from treatment of slag & black drosses	11.5	2.4	MT/A		CHWTSDF
5	Container Sludge	33.2	1.2	MT/A		CHWTSDF
6	Empty Barrels/dru ms	33.3	3000	Nos./ A	_	Sale to MPCB authorized recycler

SRO Satara/R/L/52493000

7	ETP Sludge	34.3	2.9	MT/A		CHWTSDF
8	Process Dust	13.1	0.5	MT/A		Sale to MPCB authorized recycler
9	Tank Bottom sludge	3.3	2.0	MT/A		CHWTSDF
10	Spent Resin	34.2	0.5	MT/A		CHWTSDF
11	E Waste	_	0.5	MT/A	-	Sale to MPCB authorized recycler
12	Used Lead acid batteries	B3 (Sch.II)	100	Nos./ A	·	Return to supplier/manufactur er/ Sale to MPCB authorized recycler

# 7. Conditions under Non Hazardous and disposal of non hazardous waste: NATURE, QUANTITY AND METHOD OF DISPOSAL OF NON-HAZARDOUS SOLID WASTE

		<del></del>	
Sr.No.	Type of Waste	Disposed Quantity (Tones/Yr)	Disposal Method and its destination
1	Aluminium Boring	45.0	
2	Card Board /Paper Scrap	30.0	
3	Copper Wire Scrap	25.0	Disposal to scrap dealers through Tender/Auction
4	Misc. Scrap	30.0	
5	Metal Scrap	40.0	
6	C.I. Boring	3000.0	
7.	Steel Scrap	110.0	
8	Wooden Scrap	240.0	Disposal to scrap dealers
.9	Plastic Scrap	30.0	through Tender/Auction
10	Plastic Scrap /MS Scrap	36,000	

7. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.

SRO Satara/R/L/52493000

Page .

8. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.

For and on behalf of the Maharashtra Pollution Control Board

> (Rajeev Kumar Mital, IAS) Member Secretary

#### Received Consent fee of -

Sr. No.	Amount (Rs.)	DD.N6.	jÿ∵ Date	Drawn On
1.	2,40,000/-	001859	21/10/2013	IDBI Bank

#### Copy to:

- 1. Regional Officer, MPCB, Pune and Sub-Regional Officer, MPCB, Satara: They are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updation purposes.

SRO Satara/R/L/52493000

### Schedule-I

# Terms & conditions for compliance of Water Pollution Control:

- 1) A] As per your application, you are provided Combined Effluent Treatment Plant for Trade & Sewage effluent of Capacity 85.0 CMD.
  - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr No.	Parameters	Standards proposited by D
	l. Compulsory Parameters	Standards prescribed by Board (If any) Limiting Concentration in mg/l, except for pH
_01	рН	5.5 to 9.0
02	Suspended Solids	100
03	BOD (3 days 27oC)	100
04	COD	250
05	Oil & Grease	10
06	Total Dissolved Solids	2100
07	Chloride	600
80	Sulphates	1000
09	Copper	3.0
10	Zinc	5.0
11	Iron(As Fe)	3.0
12	Total Metal	10.0
		337

- C) The treated effluent shall be recycle up to maximum extent and remaining shall be used on land for gardening. In no case, effluent shall find its way for gardening/outside factory premises.
- 2) A.J As per your consent application, you have provided the Combined Effluent Treatment Plant for Trade & Sewage effluent of Capacity 85.0 CMD.
  - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

(1)	Suspended Solids.	Not to exceed	100	mg/l.
(2)	BOD 3 days 27oC.	Not to exceed	100	mg/l.

SRO Satara/R/L/52493000

- C] The treated sewage shall be disposed on land for gardening
- D] In case the treatment system is combined for trade effluent and sewage then the standards and disposal path prescribed at sr. no.1 B & C of schedule I shall be applicable.
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition thereto.
- 4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
- 5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr.	Purpose for water consumed	Water consumption
no.		quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler	20.0
	feed	
2.	Domestic purpose	55.0
3.	Processing whereby water gets polluted &	36.0
	pollutants are easily biodegradable	
4.	Processing whereby water gets polluted &	
	pollutants are not easily biodegradable and are	
	toxic	
5.	Gardening	65.0

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time.

SRO Satara/R/L/52493000

### Schedule-II

# Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have proposed to install/ provided the Air pollution control (APC)system and also proposed to erect / erected following stack (s) and to observe the following fuel pattern-

	APC 🔠	Height	Type of	Quantity	S %::	SO <sub>2</sub> *
To Life	System	in	Fuel	& UoM		Kg/Day
		Mtrs.				
Boiler	Dust	17	F.O.	12	3.07%	25.92
(Thermopack)	Collector			Lit./Hrs.		
Decarb Furnace		12.5	LPG	16 Kg/Hr	0.02	
- 2nos.	Exhaust	(Each)			%	
Varnish Oven	Stack	8.5	HSD	10 Lit/Hr	1 %	4.8
Stack Welding		8.5	<b>HSD</b>	10 Lit/Hr	1 %	4.8
DG Set (750	Stack	3.5	HSD	28	1 %	13.44
KVA) – 2 Nos.		(Each)	•	kgs./hrs.		
		above		(each),		
		the		,		
4		roof			•	
DG Set ( 110	Stack	2.5	HSD	6.0 lit/Hrs	1 %	2.88
KVA)		above				
		the				
		roof		·	·	
	Boiler (Thermopack) Decarb Furnace - 2nos. Varnish Oven Stack Welding DG Set (750 KVA) – 2 Nos.	Boiler (Thermopack) Collector  Decarb Furnace - 2nos. Exhaust  Varnish Oven Stack  Stack Welding  DG Set (750 Stack  KVA) – 2 Nos.  DG Set (110 Stack	To System in Mitrs.  Boiler Dust 17 (Thermopack) Collector 12.5 (Each) Decarb Furnace 2 12.5 (Each) Varnish Oven Stack 8.5 Stack Welding 8.5 DG Set (750 Stack 3.5 (Each) KVA) – 2 Nos. (Each) DG Set (110 Stack 2.5 above the stack well above	To System in Fuel  Mitrs:  Boiler   Dust   17   F.O.   (Thermopack)   Collector   Decarb Furnace   12.5   LPG   - 2nos.   Exhaust   (Each)   Varnish Oven   Stack   8.5   HSD   Stack Welding   8.5   HSD   DG Set (750   Stack   3.5   HSD   KVA) - 2 Nos.   (Each)   above   the   roof   DG Set (110   Stack   2.5   HSD   KVA)   above   the	To System in Fuel & UoM  Mitrs.  Boiler (Thermopack) Collector Decarb Furnace - 2nos.  Varnish Oven Stack 8.5 HSD 10 Lit/Hr  Stack Welding B.5 HSD 10 Lit/Hr  DG Set (750 Stack 3.5 HSD 28 Kgs./hrs. (each),  KVA) - 2 Nos.  DG Set (110 Stack 2.5 HSD 6.0 lit/Hrs  above the roof  DG Set (110 Stack 2.5 HSD 6.0 lit/Hrs  above the roof	To         System Mtrs.         in Mtrs.         Fuel Mtrs.         & UoM           Boiler (Thermopack)         Dust Collector         17 F.O.         12 3.07% Lit./Hrs.           Decarb Furnace - 2nos.         12.5 LPG 16 Kg/Hr 0.02 %           Varnish Oven Stack         8.5 HSD 10 Lit/Hr 1 %           Stack Welding DG Set (750 KVA) - 2 Nos.         Stack (Each) (Each) kgs./hrs. (each), the roof           DG Set (110 Stack KVA)         2.5 HSD 6.0 lit/Hrs 1 % Agove the the roof           DG Set (110 KVA)         40 Lit/Hr 1 % Agove the the roof           DG Set (110 KVA)         50 LPG 16 Kg/Hr 0.02 % Agove the roof           Leach Manual Roof Roof Roof Roof Roof Roof Roof Roo

- 2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	150 mg/Nm <sup>3</sup> .	
SO <sub>2</sub>	Not to exceed	52.0 Kg/Day	

SRO Satara/R/L/52493000

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

# Schedule-III Details of Bank Guarantees

Sr.	Consent	Amt of	Submissi	Purpose of BG	Compliance	Validity
No.	(C to	BG	on Period		Period	Date
	E/O/R)	Imposed			் ஆ <sub>ன</sub> ் ந்	
1	Renewal	5.0 Lakh.	15 days	Operation &		31.03.2017.
	of			maintenance of		
	consent		€	pollution control		
				system.		

SRO Satara/R/L/52493000

### Schedule-IV

### General Conditions:

The following general conditions shall apply as per the type of the industry (Product wise).

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- 3) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 5) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

SRO Satara/R/L/52493000

- 8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30<sup>th</sup> June of every year.
- 10)An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall obtain Consent to Operate from Maharashtra Pollution Control Board before actual commencement of the Unit/ Activity (in case of Consent to establish).
- 12) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent (in case of Renewal of consent).
- 13)Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(<a href="www.mpcb.gov.in">www.mpcb.gov.in</a>).
- 14) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 15)Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 16) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 17) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

18) Conditions for D.G. Set

SRO Satara/R/L/52493000

- a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f) D.G. Set shall be operated only in case of power failure.
- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 19) The industry should not cause any nuisance in surrounding area.
- 20) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 21) The applicant shall maintain good housekeeping.
- 22) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31<sup>st</sup> March of the year and number of trees planted by September end.
- 23) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.

SRO Satara/R/L/52493000

. Page 11

- 24) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 25) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 26) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 27)The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 28) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dated . 16.11.2009 as amended.

----0000----

SRO Satara/R/L/52493000