## AHARASHTRA POLLUTION CONTROL BOARD

Phone: 4010437/4020781

/4037124/4035273

Fax

24044532/4024068 /4023516

Email

enquiry@mpcb.gov.in

Visit At :

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E).

Mumbai - 400 022

Consent No: Format 1.0/ BO/CAC-Cell/EIC No:-NM-4855-13/18th CAC/CAC-4227 Date- 05/05/2013

To,

M/s Siemens Ltd.

Plot no. 1, MIDC, TTC Industrial Area, Airoli. Thane Belapur Road, Navi Mumbai 400 708

Subject: Renewal of Consent under RED category.

Ref

: 1. Earlier Consent granted vide no. BO/PCI-II/EIC NO. NM-1234-08/R/CC-50

Date: 1/10/2009

2. Minutes of CAC meeting held on 15.04.2014

Your application: CR1310000336

Dated: 03/10/2013

For: Renewal of Consent

under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

The consent is granted for a period from 01/11/2013 to 30/04/2016.

2. The actual capital investment of the existing industry is Rs.258.50/- Crs. (As per C. A. Certificate submitted by industry)

3. The Consent is valid for the manufacture of -

Sr. No.	Product / By-Product Name	Maximum Quantity in MT/A
1	Electrical Motors	As per order
2	Traction Motors ( )	As per order
3	Switchgear Items	As per order
4	LT & HT Switchboards	As per order
5	Transformer	As per order

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. no.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
1.	Trade effluent	4.2	As per Schedule –I	To STP
2.	Domestic effluent	400	As per Schedule -I	60% treated sewage shall be recycled for flushing, fire fighting, cooling etc and remaining shall be used on Ind for gardening

Conditions under Air (P& CP) Act. 1981 for air emissions.

Sr.	Description of stack /	Number of Stack	Standards to be	
no.	source		achieved	
1.	Process vents	28	As per Schedule -II	
2.	DG set	7	As per Schedule -II	
3.	(Oven)	11	As per Schedule -II	

6. Conditions about Non Hazardous Wastes:

Sr. no.	Type Of Waste	Quantity & UoM	Treatment	Disposal
1	Ferrous scrap	į.	No	Sale
2	Paper scrap	-	No	Reuse for packing purpose
3	Wood scrap	-	No	Şale
4	Solid waste from canteen		No	Send to Piggery
5	Printer ribbon cartridge		No	Returned back to supplier
6	Recyclable plastic	Ť	No	Sale
7	Other miscellaneous non hazardous waste	· †	No	NMMC
8	Fluorescent light	<del>.</del>	No 🔏	Sale to Recycler

7. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr. No.		Category	Quantity	UOM	Treatment	Disposal
1	Used/ spend oil	5.1	850	kg/day		TTCWMA
2	Used Coolant & Waste Oil	5.2	660	kg/day		TTCWMA
3	Oil soaked cloth	5.2	121	kg/day		TTCWMA
4	Oil Soaked Saw-dust	5.2	2	kg/day		TTCWMA
5	Oil Filters	5.2	1,4	kg/day		TTCWMA
6	Oil Contaminated parts	5.2	41	kg/day		TTCWMA
7	Sparking Carbon	5.2	0.1	kg/day		TTCWMA
8	Grinding Sludge	В3	27	kg/day		TTCWMA
9	Paint Sludge	21.1	54	kg/day		TTCWMA
10	Varnish	21.1	45	kg/day	,	TTCWMA
11	Thermoset Plastic	21.1	115	kg/day		TTCWMA
12	Asbestos Gaskets/ Seals	B21	As and wh	*	·	TTEWMA
13	Batteries (pencil cells & Lead Acid batteries)	C14	As and wh generated	₩ ₹		Sent to TTCWMA/Auth Recyclers
14	Empty containers of Hazardous	33.3	As and who	-		TTCWMA



	Chemicals				
15	Solder Waste	B4	As and who	-	Sent to TTCWMA/Auth Recyclers
16	Thermocol	21.1	As and wh	â	Sent to TTCWMA
17	Miscellaneous Waste E.g. Mica, Foam, Safety Shoes, Printer cartridge, Printer ribbon, etc.	included by	As and wh generated		TTCWMA
18	Waste Deionising Resin	23.1	0.75	kg/day	TTCWMA
19	Resin (Liquid)	23.1	45	kg/day	TTCWMA
20	Non Ferrous Scrap		As and wh generated	-	CPCB/MPCB Authorised re- processor
21	E -Waste electronic & electrical equipment	Schedule 4	As and wh		Sale to authorized recycler/ re- processor

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.

For and on behalf of the Maharashtra Pollution Control Board

(Rajeev Kumar Mital, IAS) Member Secretary

Received Consent fee of -

Sr.	Amount(Rs.)	DD. No.	Date	Drawn On
No.				
1	23,67,106/-	282130	17.09.2013	Deutsche Bank
2	8,16,000/-	304297	22.01.2014	Deutsche Bank

#### Copy to:

- 1. Regional Officer -Navi Mumbai and Sub-Regional Officer-Navi Mumbai-II, MPCB- They are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updation purposes.

#### Schedule-I

#### Terms & conditions for compliance of Water Pollution Control:

1) A] As per your application, you have provided the Effluent Treatment Plant (ETP).

B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

	Parameters	Standards prescribed by Board (If any) Limiting Concentration in mg/l, except for pH			
	I. Compulsory Parameters				
01	рН	6.0-8.5			
02	Oil & Grease	10 mg/l			
03	BOD (3 days 27oC)	100 mg/l			
04	Total Dissolved Solids	2100 mg/l			
05	Suspended Solids	100 mg/l			
06	COD	250 mg/l			

- C) The treated effluent shall be disposed for further treatment in STP
- 2) A.] As per your consent application, you have provided the sewage treatment system with the design capacity of 500 CMD.
  - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

(1) Suspended Solids.

Not to exceed

100 mg/l.

(2) BOD 3 days 27oC.

Not to exceed

100 mg/l.

- C] The 60% treated sewage shall be recycled for flushing, fire fighting, cooling etc and remaining shall be used on own land of 15.56 acres for gardening
- D] In case the treatment system is combined for trade effluent and sewage then the standards and disposal path prescribed at sr. no.1 B & C of schedule I shall be applicable.
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition thereto.
- 4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

Ruth

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	30
2.	Domestic purpose	600
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	5
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	NIL

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/Environmental Clearance / CREP guidelines.

White

## Schedule-II

# Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached To	APC System	Height in			s %	SO <sub>2</sub>
1	Motor -Liquid Spraý Paint booth 1	Water	Mtrs. 8.3	NA NA	VoM NA		Kg/Day
2	Motor -Liquid Spray Paint booth 1	Water	8.3	NA	NA	***	
3	Motor -Liquid Spray Paint booth 2	Water	9.5	NA	NA		
4	Motor -Liquid Spray Paint booth 2	Water curtails & Filters	9.5	NA	NA		
5	Motor -Liquid Spray Paint booth 3	Water curtails & Filters	10	NA	NA		
6	Motor-Liquid Spray Paint booth 3	Water curtails & Filters	10	NA	NA		
7	Housing heating Oven (Assembly)	Dilution Exhaust	8.5	NA	NA		
8	Exhaust of Motor Varnishing Oven 1	Dilution Exhaust	9.2	NA	NA		
9	Exhaust of Motor Varnishing Oven 2	Dilution Exhaust	9.2	NA	NA	·	
10	Exhaust of Motor Varnishing Oven 3	Dilution Exhaust	7	NA	NA		
	Exhaust of Motor Varnishing Oven 4	Dilution Exhaust	7	NA	NA		
12	Exhaust of VPI Plant 1 (old)	Dilution Exhaust	7.3	NA	NA		
13	Exhaust of VPI Plant 1 (old)	Dilution Exhaust	7.3	NA	NA		
14	Exhaust of MV		8.3	NA	NA		
15	PARTICIPATION OF THE PARTICIPA	Dilution Exhaust	4.5	NA	NA		·

Simens Ltd, SRO Navi Mumbai II/I/R/L/49148000

Page 6 of 12

16	Exhaust of MV	Dilution	9.5	NA	NA NA	1	T
	VPI Plant- High	Exhaust	7.3	IN/A	NA		,
	pressure	Zama ast				1	
No. 200 do	release pipe						
17	Exhaust of MV	Dilution	8.3	NA	NA		1
	VPI plant	Exhaust					
	Vacuum pump						
18	FT2015 resin Exhaust of MV	Dilution	8.3	1		<del> </del>	
10	VPI plant	Exhaust	8.3	NA NA	NA		
	pressure	2maast				1	
	release line of						
1000	resin tanks						
19	Exhaust of	Dilution	6.5	NA	NA		
	rotor brazing	Exhaust					,
20	machine. Exhaust of	Dilution	3				
20	Packeting	Exhaust	3	NA	NA		
	heating Oven 2.	Danaust				1	
21	VPI plant -High	Depressu	8.2	NA	NA		
	pressure	rise	7				
	release pipe		300000				
22	VPI plant -High	Depressu	8.2	NA	NA		
	pressure release pipe	rise					
23	VPI Plant	Dilution	8.3	NA	NA		
7759-776	vaccum pump	Exhaust &	0.0		l Ma		
	no 1&2	Stack					
	20.00.000	Height					
24	Exhaust of	Dilution	8.3	NA NA	NA		
	baking oven no	Exhaust					
25	Exhaust of	Dilution	8.3	NA	NA		
=0	baking oven	Exhaust	0.5	IVA	IVA		
	no.2						
26	Exhaust of	Dilution	8.3	NA	NA		
		Exhaust					
27	no.3 Hand washing	Dilation	0.3				
Z/	booth exhaust	Dilution Exhaust	8.3	NA	NA		
48.	no.1	Exilaust					
28	Hand washing	Dilution	8.3	Diesel	1 Lit/Hr	1%	0.48
	booth exhaust	Exhaust &	54/5/07/	-7 80 80 87 87 84 77 87		-/0	V
	no.2	Stack					
20		Height	- <u> </u>	240	100		
29	Exhaust of	Dilution	3	NA	NA		
	Packeting heating Oven 1	Exhaust			.		
30	Rotor washing	Dilution	6.5	NA	NA		
	booth	Exhaust	1.00,774	(196 <del>)</del> (197)	ন্ত্ৰীকৃত্ৰী প্ৰক		
31	Exhaust of	Dilution	8.3	NA	NA		
	Insulation	Exhaust			·	ſ	
22	burning oven.	TA7 .	7		- <u></u>		
32	Switchgear - liquid spray	Water curtails &	6	NA	NA		
	paint booth-1	Filters			7		
	Programme Appropriate					,	

Simens Ltd, SRO Navi Mumbai II/I/R/L/49148000

......

W pt

Page 7 of 12

33	860 KVA	Dilution	12	Diesel	10015/0	1404	T 200
	Generator stack		< 200 Att	Diesei	160 Lit/Hr	1%	76.8
	located in Main		-	1		1	
	Generator	Height					
	room	Height					
34	860 KVA	Dilution	12	Diesel	160 Lit/Hr	104	
	Generator stack		2407977100S	Diesei	TOO FIL HE	1%	76.8
	located in Main	Stack			İ	£ 7.	1
	Generator 7.	Height	į		İ	7.	
	room	rieight					
35	125 KVA	Dilution	2.8	Diesel	25 Lit/Hr	10/	+
	Generator stack			Diesei	25 Lit/m	1%	12
	located near	Stack	1	İ			1
	central	Height					
	Building	l			ĺ		<b>&gt;</b>
36	160 kva	Dilution	4.5	Diesel	30 Lit/Hr	130/	1
	generator stack	Exhaust &	1 2,50	Dicsei	SO PITA HE	1%	14.4
	located	Stack				•	
	opposite	Height	· <b>[</b>				
	canteen	, respire					
37	1010 KVA	Dilution	10	Diesel	90571161		
	Generator stack	Exhaust &	10	Diesei	205 Lit/Hr	1%	98.4
	located near	Stack				İ	
•	R&D Center	Height				İ	
38	1010 KVA	Dilution	10	D:I			
<i>3.</i>	Generator stack	Exhaust &	TU	Diesel	205 Lit/Hr	1%	98.4
	located near	Stack					•
	R&D Center	Height					
39	VPI winding	Stack	6	NA NA			
	VPD plant	Height #	U	NA	NA		
	vacuum Pump	neight					
40	VPI Active part	Stack	6	NA		<del></del>	
136-00-27	VPD plant	Height		INA.	NA	<b>.</b>	
	vacuum pump	ricigni					
	no-1		ı				
41		Stack	42	HSD	87.6 Kg/Hr	104	44.00
	Heater *	Height	. 700	Пор	07.0 Kg/HF	1%	41.28
42	Vacuum	Oil Mist	NA	NA	NA		
	pumping	Seprator		\$15.5 <u>.</u>	1.3.0		
	system Pump-1						
43 🔪	Vacuum	Oil Mist	NA	NA	NA		
	pumping	Seprator	760767	****	WA		
	system pump-2				1		
14	Filter machine	Oil Mist	NA	NA	NA		
	vacuum	Seprator	50.00 M M	্টা জন্ম ক <sup>ৰ</sup>	1344		
	Pumps-1			1			
-5	Filter machine	Oil Mist	NA	NA	NA		·
- 1	Section Section 1981 -	Seprator	seath for	1-00-	1.734.4	1	
	pumps-2				1		
6	350 - 650 000 000 000 000 000 000 000 000 000	Dilution	12	Diesel	165 Lit/Hr	1%	79.2
- 1		Exhaust &		TERRORE RE		- /0	1 7.4
l	1111211			1	i	- 1	
	1.	Stack			1 1	- 1	

\_\_\_

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines. (Concern section shall mention specific control equipments)

3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate Not to exceed 150 mg/Nm³.

4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution control equipment.

5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of

any control equipment, other in whole or in part is necessary).

(V pt)

Simens Ltd, SRO Navi Mumbai II/I/R/L/49148000

Page 9 of 12

# Schedule-III Details of Bank Guarantees

Sr.	Consent	Amt of BG	Submission	Purpose of BG	Compliance	Validity
No.	(C to E/O/R)	Imposed	Period		Period	Date
1	C to R	05/- Lakhs		O & M of Pollution control Systems		31.08.20 16

Managhtian Control Board

With

#### Schedule-IV

# **General Conditions:**

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker if applicable.

3) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.

- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.
- 5) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled

- 9) /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 10) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazarsous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 11) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 12) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- 13) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 14) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 15) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 16) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

Page 11 of 12

- 17) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 18) Conditions for D.G. Set
- Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f) D.G. Set shall be operated only in case of power failure.
- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 19) The industry should not cause any nuisance in surrounding area.
- 20) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 21) The applicant shall maintain good housekeeping.
- 22) The applicant shall bring minimum 33% of the available open land under green coverage/plantation. The applicant shall submit a statement on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end, with the Environment Statement.
- 23) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 24) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 25) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 26) The industry shall submit quarterly statement in respect of industries' obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can be downloaded from MPCB official site).
- 27) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 28) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

Wint

----0000-----