MAHARASHTRA POLLUTION CONTROL BOARD

Phone :

Fax

1

Email : Visit At : 4010437/4020781 /4037124/4035273 24044532/4024068 /4023516 enguiry@mpcb.gov.in

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E), Mumbai - 400 022

Consent No: Format 1.0/BO/CAC-CELL/PN-21215-14/E/CAC-4702 Date- 9/05/2014. To, M/s. Vitthal Refined Sugars Ltd., G. No. 274, 248,252, 254, 256, A/p - Pande,

Tal. Karmala, Dist. Solapur.

Subject: Consent to Establish of Sugar & Co-generation unit under RED category.

Ref : 1. Minutes of CAC meeting held on 12.05.2014.

Your application: CE1403000534.

Dated: 12/03/2014.

For: Consent to Establish of Sugar & Co-generation unit.

under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- 1. The consent is granted for a period up to Upto commissioning of the unit or 5 yrs. whichever is earlier.
- 2. The Proposed capital investment of the industry is Rs. 133.16 Cr. (As per the undertaking submitted by industry)

3. The Consent is valid for the manufacture of -

Sr. No	Product / By-Product Name	Maximum Quantity in MT/M
1	Sugar	18000
2	Pressmud	6000
3	Molasses	6000
4	Baggase	52500
5	Electricity Power (Co-Gen)	26 MW.

(The cane crushing Capacity of Sugar Industry shall not exceed 5000 TCD)

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

[Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
	1.	Trade effluent	627.0 (Sugar 522 +Co-gen 105)	As per Schedule -I	On land for gardening
	2.	Domestic effluent		As per Schedule -I	On land for gardening

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr. no.	Description of stack / source	Number of Stack	Standards to be achieve
1.	Boiler (80 TPH)	1 no.	As per Schedule -II
2.	D.G. set of 500 KVA.	1 no.	As per Schedule -II

M/s. Vitthal Refined Sugars Ltd., SRO Solapur /I/R/L/99487000

Page 1of 8

6. Conditions about Non Hazardous Wastes:

Sr. no.	Type Of Waste	Quantity & UoM	Treatment	Disposal
1	Fly ash	980 MT/M	-	By Sale.
2	ETP Sludge	05 MT/D	-	Used as Manure

7. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr.	Type Of Waste	Category	Quantity	UOM	Treatment	Disposal
No.						TT: 1. 1. 1
1	Used/ Spent oil	5.1	100.0	Ltrs./M	Mixed with	Fired in boiler
					Bagasse	

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. The applicant should not take any effective steps for implementation of the project before obtaining Environmental Clearance as per EIA Notification 2006 and amendments thereto. As per Para 2 of EIA notification dated-14/09/2006, the effective steps include starting of any construction work or preparation of land by the project management. However as clarified by the MoEF vide office memorandum no. J-1103/41/2006-IA.II(I); Dated-19/8/2010,fencing of the site to protect it from getting encroached & construction of temporary shed(s) for the guard(s) & acquisition of land shall not be treated as an effective steps.
- 10. Industry shall have to submit double amount of BG as per the matrix for achieving the standards to be obtained while granting C to 1st Operate, if the ETP units are not right sized.
- 11. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.
- 12. This Consent is Consent is issued on the basis of distance certificate issued by Executive Engineer, Irrigation Dept. Solapur vide letter 1080/2014 dated 23.2.2014 i.e. distance from operational area to average HFL of River Sina A-II class is 5 km.

For and on behalf of the Maharashtra Pollution Control Board (Rajeev Kumar Mital, IAS.) Member Secretary Received Consent fee of -Drawn On Date Amount(Rs.) DD. No. Sr. No. 20.01.2014 State Bank of India. 564537 Rs. 2,66,420/-1 Copy to: 1. Regional Officer MPC Board, Pune & Sub-Regional Officer, M.P.C. Board, Solapur - They are directed to ensure the compliance of the consent conditions. 2. Chief Accounts Officer, MPCB, Mumbai.

3. CAC desk- for record & website updation purposes.

M/s. Vitthal Refined Sugars Ltd., SRO Solapur /I/R/L/99487000

Page 2of 8

Sch	edu	le-I

Terms & conditions for compliance of Water Pollution Control:

- 1) A] As per your application, you have proposed to install the Effluent Treatment Plant (ETP) with the design capacity of 1000 CMD.
 - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act. 1986 and Rules made there under from time to time, whichever is stringent.

Sr No.	Parameters	Standards prescribed by Board (If any)	
		Limiting Concentration in mg/l, except for p	H
01	рН	5.5-9.0	ŝ.,
02	Oil & Grease	10	j.
03	B. O. D.	100	
04	C. O. D.	250	\wedge
05	T. D. S.	2100	\$ ×
06	Chlorides	600	
07	Sulphates	1000	
08	Suspended Solid	100	

- C) The treated effluent 522 CMD of sugar shall be disposed on own land of 40 acres for gardening/irrigation & 105 CMD of the co-gen shall be recycled 100% in the process.
- D) Industry shall provide separate primary treatment for effluent generation from DM plant.
- E] CREP conditions for Sugar Factory
- i. Operation of ETP shall be started at least one month before starting of cane crushing to achieve desired MLSS. So as to meet prescribed standards from day one the operation of mill.
- ii. Waste water generation shall be reduced to 100 liters per tone of cane crushed.
- iii. Industry shall achieve zero discharge into in land surface water bodies.
- iv. 15 days storage capacity tank shall be provided for treated effluent to take care of no demand for irrigation.
 - F] Industry to make necessary arrangement to cover the effluent collection system and to avoid the ingress of Bagasse other material.
 - G] Industry shall provide flow meter at Inlet of ETP of Sugar & Co-Gen Units, and to maintain the record with data logging system.
- 2) A] As per your consent application, you have proposed to provide the sewage treatment plant for treatment of domestic effluent.
 - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

(1)	Suspended Solids.	Not to exceed	100	mg/l.
(2)	BOD 3 days 27oC.	Not to exceed	100	mg/l.

C] The treated sewage 16 CMD shall be disposed on land of 40 acres for gardening /irrigation.

M/s. Vitthal Refined Sugars Ltd., SRO Solapur /1/R/L/99487000

Page 3of 8

- 3) The industry shall have bilateral agreement with the farmers on whose land the treated effluent is used for irrigation purposes and a copy of the agreements with validity shall be submitted to the Regional/Sub- Regional Office of the Board.
- 4) The industry shall create Environmental Cell by appointing an Environmental Engineer, Chemist and Agriculture expert for looking after day to day activities related to Environment and irrigation field where treated effluent is used for irrigation.

5) CONDITIONS FOR MOLASSES STORAGE:

- (i) The molasses shall be properly collected and stored in steel tanks which shall be leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- (ii) The capacity of tanks for storage of molasses shall be such that it will take care of bumper production of sugar, non-lifting of molasses etc.
- (iii) All the area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- (iv) Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board. Intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- (v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near /on the tank.
- (vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- 6) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	309.00
2.	Domestic purpose	20.00
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	891.00
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	

.7) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act,1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.

M/s. Vitthal Refined Sugars Ltd., SRO Solapur /1/R/L/99487000

Page 4of 8

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have proposed to install the Air pollution control (APC)system and also proposed to erect following stack (s) and to observe the following fuel pattern-

	Stack						
No.	Attached To	System	in Mtrs.	Fuel	y & UoM	%	Kg/Day
1.	Boiler (150 TPH)	ESP	85	Bagasse	1800 MT/D.	0.2 %	7200
2.	D.G. set of 500 KVA.		5.0	HSD	1560 Ltrs./D	1%	31.2

- 2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines. (Concern section shall mention specific control equipments)
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate	Not to exceed	150 mg/Nm^3 .
matter		

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

Schedule-III

Bank Guarantee Details

Sr. No.	Amt of BG Imposed	Submission Period	Purpose of BG	Complianc e Period	Validity Date
1	10/- Lakhs	15 days.	Compliance of EC condition to not to take any effective steps for implementation of the project prior to obtaining EC.	Obtaining EC	1 year
		- - -			
				6	

<u>Schedule-IV</u> <u>General Conditions</u>:

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 3) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 4) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 5) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 6) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 7) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled
- 8) /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazarsous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall obtain Consent to Operate from Maharashtra Pollution Control Board before actual commencement of the Unit/ Activity.
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(<u>www.mpcb.gov.in</u>).
- 13) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 14) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 15) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register_showing consumption of chemicals used for treatment shall be maintained.
- 16) Conditions for D.G. Set
 - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

Page 7of 8

M/s. Vitthal Refined Sugars Ltd., SRO Solapur /l/R/L/99487000

- b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f) D.G. Set shall be operated only in case of power failure.
- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 17) The industry should not cause any nuisance in surrounding area.
- 18) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 19) The applicant shall maintain good housekeeping.
- 20) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a statement on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end, with the Environment Statement.
- 21) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 22) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 23) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 24) The industry shall submit quarterly statement in respect of industries' obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can be downloaded from MPCB official site).
- 25) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.
- 27) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.
- 28) The industry shall ensure replacement of <u>pollu</u>tion control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

----0000-----

Page 8of 8

M/s. Vitthal Refined Sugars Ltd., SRO Solapur /I/R/L/99487000

Ĩ