MAHARASHATRA POLLUTION CONTROL BOARD

Phone :

4010437/4020781

/4037124/4035273

Fax

24044532/4024068 /4023516

Email

ast@mpcb.gov.in

Visit At :

http://mpcb.gov.in

MAHARASHTRA

Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Mumbai - 400 022

Red/L.S.I

Date: 04/06/2014

Consent No: BO/AST/R/EIC NO.NM-4067-12/CC 65527

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Shirdi Chemicals P. Ltd Plot No. C-118, TTC Indl. Area, MIDC Pawane, Navi Mumbai

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.05.2016

M.

2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum	UOM
Seamon to		Quantity	
1	2-(2 Hydroxy-3,5 Dicumyl) Benzotriazole	5.00	MT/M
2	2,4 Dicumyl Phenol	1.00	MT/M
3	PPP-BP (Phenolphthanilide)	20.00	MT/M
4	CGL-008/5- (4-Dimethylaminobenzylidene)	1.00	MT/M
	Pyaimidine-2,4,6-trione		
5	Anysoyl Chloride	10.00	MT/M
6	3- (Chloroiminodibenzyl)	1.00	MT/M
7	Isobutyryl Chloride	10.00	MT/M
8	Clomipramine Hydrochloride	0.5	MT/M
9	Methyl Hydroquinone	20.00	MT/M
10	Bis (Phenyl Acetyl) Disulphide or PADS or	1.00	MT/M
	Phenyl Acetyl Disulfide		
11	Bromo Acetaldehyde Dimethyl Acetal	1.00	MT/M
12	Metrondiazole Benzoate IP/BP	15.00	MT/M
13	DMBPC (4,4 Cycloheylidenebis [2-methyl	8.00	MT/M
- 2	phenol])	123	<u> </u>
14	N-methyl Formanilide	5.00	MT/M
15	Methylamino Acetaldeyde Dimethyl Acetal	1.00	MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed $8.00\ M^3$.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 4.0 M³.

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

		Between	6.5 to	0.8.5		
01	pH			- C		
02	Suspended Solids	Not to exceed	100	mg/l		
03	BOD 3 days 27° C	Not to exceed	100	mg/l		
04	COD	Not to exceed	250	mg/l		
05	Oil & Grease	Not to exceed	10	mg/l		
06	Chlorides	Not to exceed	600			
07	Sulphates	Not to exceed	1000	mg/l		
08	TDS	Not to exceed	2100	mg/l		
09	Free Ammonia	Not to exceed	5	mg/l		
10	% Sodium	Not to exceed	60 %_	mg/l		
-		Not to exceed	5	mg/l		
11	Phenol Not to exceed 5 Ing/1					
12	Bioassay test 90 % survival of fish after first 96 hours in 100 %					
	effluent					

- (iv) Trade Effluent Disposal: The treated effluent shall be recycled / reused to the maximum extent and remaining shall be disposed into CETP.
- (v) Sewage Effluent Treatment. The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Sugnanded Salids	Not to exceed	100	mg/l.
(1) (2)	Suspended Solids BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

Non-Haza	rdous Sond Waste	5.		D. 1
C. No	Type Of Waste	Quantity UOM	Treatment	Disposal
Dr. 110.	Type Of Waste			
		N.A		

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

5.00 CMD (i) Domestic purpose

(ii) Water gets Polluted & 13.00 CMD Pollutants are Biodegradable ...

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ...

0.00 CMD

(iv) Industrial Cooling, spraying in mine pits or boiler feed

53.00CMD

(v) Gardening

5.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system (i) consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:

- Scrubber of sufficient capacity should be provided to limit the emissions and operated properly.
- There shall not be any secondary (fugitive) emissions. Π.

b. Standards for Emissions of Air Pollutants:

(i) SPM/TPM	Not to exceed	150.0 mg/Nm3
(ii) SO2	Not to exceed	10.8 Kg/day
(iii)SO2 (Process)	Not to exceed	50 ppm
(iv) NOx (Process)	Not to exceed	50 ppm
(v) NH3 (Process)	Not to exceed	50. mg/Nm3
(vi) Cl2	Not to exceed	03 ppm
(1) 012		

Standards for Stack Emissions:

The applicant shall observe the following fuel pattern:-(i)

Sr. No.	Type Of Fuel	Quantity	UOM
1		300.00	Lit/Day
2	Diesel	600.00	Ltr/M

applicant shall erect the chimney(s) of the following (ii) pecifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Scrubber	22.00
2	Boiler	18.00
3	D.G Set (250 KVA)	3.50

- The applicant shall provide ports in the chimney/(s) and facilities such as (iii) ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- The industry shall take adequate measures for control of noise levels from "; (iv) its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70

dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- The industry should monitor stack emissions and ambient air quality regularly.

C) Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall handle hazardous wastes as specified below.

(i)	- Th	Industry shall handle haza Of Waste	Quantity	UOM	
Sr. No.	Type 20,3 Di	stillation residues	24.00	MT/Y	Incineration at CHWTSD
2	28.2	Spent catalyst / spent carbon	1.20	MT/Y	Recycled through MPCB authorized party
**		Spent catalyst / spent carbon	147.84	MT/Y	CHWTSDF Taloja
3	28.2	Spent catalyst / spent cars	12.00	MT/Y	CHWTSDF TAloja
4	28.1	Residues and wastes*	12.00	MT/Y	MPCB authorized solvent
5	28.5	Spent organic solvents	12.00	1	reprocessor
6	28.4	Spent mother liquor	250.00	MT/Y	In-plant recovery solvent/Effluent ETP/CHWTSDF
7	34.3	Chemical sludge from wa	2.88	MT/Y	CHWTSDF
	water	treatment	b 3 00	MT/Y	CHWTSIF
8	35.1 have	Filters and filter material worganic liquid	0.00		

Treatment: - NIL (ii)

- The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- 6. Whenever due to any accident or gas leakage or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of Industry, Safety and Health, Police Station, Fire Brigade, Directorate of Health Services, Department of Explosives, Board and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emission and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.

7. Industry shall comply with following additional conditions:

The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

ii. The applicant shall bring minimum 33% of the available open land under green

coverage/ tree plantation.

iii. Solid waste - The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities

for disposal to dumping ground.

iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the

Board.

vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

vii. The applicant shall make an application for renewal of the consent at least 60

days before the date of the expiry of the consent.

viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

ix. As inspection book shall be opened and made available to the Board's officers

during their visit to the applicant.

x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and

air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

xii. Neither storm water nor discharge from other premises shall be allowed to mix

with the effluents from the factory.

- 10. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
- 11. If CETP does not operate efficiently and problem of pollution occurs, industry shall voluntarily stop the production or total effluent shall be reused.
- Industry shall not start manufacturing of bulk drug products till provision of adequate pollution control system & obtaining prior permission of the Board. Industry shall submit Bank Guarantee of Rs.5 lakh towards compliance of the same in favor of Regional Officer Navi Mumbai valid up to 30/09/2016.
- 13. Board has reserved right to review amend, suspend, revoke, etc. this consent same shall binding on industry.
- 14. This consent is issued as per power delegation to HOD's vide office order No 31/2013 dated 01.03.2013
- 15. The Capital investment of the industry is Rs. 11. 05 Cr. (Existing CI Rs 6. 87 Cr. Increased CI Rs 4.18 Cr)

(P.K.Mirashe) Asst. Secretary (Tech)

To, M/s Shirdi Chemicals P. Ltd Plot No. C-118, TTC Indl. Area, MIDC Pawane, Navi Mumbai

Copy to:

RO. Navi Mumbai /SRO, Navi Mumbai I.

-- They are directed to ensure the compliance of consent conditions. CAO/Cess Branch/Master file.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	250000/-	843957	30 May 2012	Canara Bank