# MAHARASHTRA POLLUTION CONTROL BOARD

Phone:

4010437/4020781

/4037124/4035273

Fax

24044532/4024068 /4023516

Email

enquiry@mpcb.gov.in

Visit At :

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near

Sion Circle, Sion (E), Mumbai - 400 022

Consent order No :- BO/JD(APC)/R/EIC No.CH-1661-14/CC-5966

Date-23.06.2014.

To.

M/s. Gupta Global Resources Ltd.,

Kh/No.175, Vill - Usgaon,

Tal & Dist: Chandrapur.

Subject: Consent to operate -RED category.

: 1. Earlier Consent granted for Coal Washery vide no. BO/JD(APC)/ EIC

No. 1240-13/R/CC- 1277 dated 20.11.2013

2. Minutes of CC meeting held on 10.06.2014.

Your application

Received Dated: 01.04.2014.

For: Renewal of Consent to operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

1. The consent is granted for a period from 01.04.2014 to 31.03.2015.

The actual capital investment of the industry is Rs.32.03 Crs. (As per C.A.Certificate dated 24.03.2014 submitted by industry along with application.

3. The Consent is valid for the manufacture of -

Sr. No.	Product / By-Product Name	Maximum Quantity
1.	Washed Coal	120000 MT/Month.
2.	Unwashed Coal	40000 MT/Month
3.	Low-grade coal	40000 MT/Month

Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. no.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
1.	Trade effluent	45.0	As per Schedule –I	Recycle
2.	Domestic effluent	3.5	As per Schedule –I	Land

5. Conditions under Air (P& CP) Act. 1981 for air emissions:

onaiu	ions under Air (f & Of) A	ct, 1901 for all emission	110.
Sr.	Description of stack /	Number of Stack	Standards to be
no.	source		achieved
1.	Crusher and Screen	1	As per Schedule -II
ļ	(common)		
2	D.G. Set 2 x 380 KVA	2	

Page 1 of 8

6. Conditions about Non Hazardous Wastes:

Sr.No	Type of waste	Quantity	Treatment	Disposal
	·			

7. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

isposai oi nazaraous	Waster .		1
Sr. Type Of Waste	Category Quantity	UOM Treatment	Disposal
No.	and the same that the same of	falga jalkasa sa kabanta katika katika	
Industry shall not	generate any haza	rdous waste	

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.
- 10. The applicant shall obtain the permission from Maharashtra Pollution Control Board before restarting the coal washery unit.

For and on behalf of the Maharashtra Pollution Control Board

> (Rajeev Kumar Mital) Member Secretary

Received Consent fee of -

Sr. No.	Amount(Rs.) DD. No. Date			Drawn On		
1	50,000/-	001670	29.03.2014	IDBI		
2	50,000/-	001643	20.03.2014	IDBI		
3	25,000/-	001651	25.03.2014	IDBI		
4	100/-	248451	27.03.2014	Bank of Maharashtra		

#### Copy to:

- 1. Regional Officer-Chandrapur and Sub-Regional Officer-Chandrapur, MPCB, They are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updation purposes.

#### Schedule-I

Terms & conditions for compliance of Water Pollution Control:

- 1) A] As per your application, you have provided the Effluent Treatment Plant (ETP) with the design capacity of 45.0 <u>CMD</u>.
  - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.
    - i] The coal washeries shall maintain the close circuit operation with zero effluent discharge.
    - If in case die to some genuine problems like periodic cleaning of the system, heavy rainfall etc. it become necessary to discharge the effluent of sewer/ land/ stream then the effluent shall conform to the following standards at the final outlet of the coal washery, for that the applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

•	• • • • • • • • • • • • • • • • • • • •		
1)	На	Between	5.5 to 9
2)	Suspended Solids	Not to exceed	100 mg/l
3)	BOD 3days 27 Deg. C.	Not to exceed	30 mg/[
<b>4</b> )	Oil & Grease	Not to exceed	10 mg/l.
5)	Total Dissolved Solids	Not to exceed	2100 mg/l.
6 <u>)</u>	Chlorides	Not to exceed	600 mg/l.
<b>7</b> )	Sulphate	Not to exceed	1000 mg/l.
8)	Phenolics	Not to exceed	1.0 mg/l

- C ) The treated effluent shall be 100% recycled in the process to achieve zero discharge. In no case effluent shall find its way for gardening/outside factory premises.
- 2) A.] As per your consent application, you have provided the sewage treatment system with the design capacity of 3.5 <u>CMD</u>.
  - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

ler from time to time, whichever is sumsome.

(1) Suspended Solids. Not to exceed 100 mg/l.

(2) BOD 3 days 27°C Not to exceed 100 mg/l.

- C] The 100% treated sewage shall be recycled for flushing, fire fighting, cooling etc
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition thereto.

4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	
2.	Domestic purpose	4.0
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	50.0
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act,1986 and rule made there under from time to time/ Environmental Clearance / CREP quidelines.

The May

Page 3 of 8

#### Schedule-II

# Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have proposed to install/ provided the Air pollution control (APC)system and also proposed to erect / erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached To	APC System	Height in Mtrs.	Type of Fuel	f Quantity & UoM	S %	SO <sub>2</sub> Kg/Day
1	Crusher & Screen	Wet scrubber	30.0#				
2	DG for 2 x 380 KVA		3.0 each	* HSD	16 Lit/Hr	1	7.68

All de-dusting stack should be at least 2.5 m above the nearest building height. Sampling Portholes and Platforms etc shall be provided as per CPCB guidelines.

Height above the roof of bldg., where it is installed.

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines. (Concern section shall mention specific control equipments)

3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

150 mg/Nm<sup>3</sup>. Not to exceed Particulate matter

4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution control equipment.

5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of

any control equipment, other in whole or in part is necessary).

Control Equipment: A]

- Coal handling plant shall be provided with Dust Collector, complete dust extraction arrangement and Automatic Water Sprinkler with fog nozzles shall be provided where necessary for dust- suppression. Dust generation points / machinery shall be covered by hoods.
- Bag filters of sufficient capacity shall be provided to coal crusher, pulverizes & all sources ii) of dust emission and operate it properly.
- Spraying of water through mist sprays and water curtains on all working area, dump area, iii) stock piles.
- Coal shall be properly covered during transportation. iv)
- The applicant shall carry out tree plantation along road side. V)
- All internal roads shall be paved and well maintained to prevent dust emissions. vi)
- Overloading of dumpers shall be avoided to prevent spillages. vii)
- Water or Water mixed chemical shall be sprayed at all strategic coal transfer points such viii) as conveyors, loading unloading points etc. As far as practically possible conveyors, transfer points etc. shall be provided with enclosures.
- The crushers/ pulverisers of the coal washeries shall be provided with enclosures, fitted ix) with suitable air pollution control measures and finally emitted through a stack of minimum height of 30 m., conforming particulate emission standard of 150 mg/Nm3 or provided with adequate water sprinkling arrangement.

M/s Gupta Global Resources Ltd, Usgaon ,Chandrapur., SRO Chandrapur/I/R/L/80261000

Page 4 of 8

- x) Water sprinkling by using fine atomizer nozzles arrangement shall be provided on the coal heaps and on land around the crushers/ pulverisers.
- xi) Area, in and around the coal washery shall be pucca either asphalted or concreted.
- xii) Green belt shall be developed along the road side, coal handling plants residential complex, office building an all around the boundary line of the coal washery.
- xiii) Storage bunkers, hoppers, rubber decks, in chutes and centrifugal chutes shall be provided with proper rubber linings.
- viv) Vehicles movement in the coal washery area shall be regulated effectively to avoid traffic congestion. High pressure horn shall be prohibited. Smoke emission form heavy duty vehicle operating in the coal washeries should confirm the standards prescribed under Motor Vehicle Rules 1989.
- xv) The coal transportation shall be done by conveyor system wherever possible or mechanically covered vehicles shall be provided for transportation of coal.

#### Bl Fugitive emission standards:

The difference in the value of suspended particulate matter, delta (D), and measured between 25 and 30 meter from the enclosure of coal crushing plant in the downward and leeward wind direction shall not exceed 150 microgram per cubic meter.

## C] Noise level standard:

Operation/ Working zone-not to exceed 85 dB(A) Leg for 8 hours exposure.

The ambient air quality standards in respect of noise as notified under Environmental (Protection) Rules, 1986 shall be followed at the boundary line of the coal washery.

- D) The applicant shall carry out ambient air quality monitoring within factory premises which should be monitored for SPM, RSPM, SO<sub>2</sub>, NOx, etc. The Annual Arithmetic Mean of minimum 104 measurements in a year taken twice a week 24 hourly at uniform interval shall conform to the National Ambient Air Quality Standards prescribed under Air (Prevention and Control of Pollution) Act, 1981 and Environment (Protection) Act, 1986. The records of results of continuous monitoring done shall be made available for inspection to the officers of the Board.
- E] The applicant shall take adequate measures for control of noise levels from its own sources as follows:

Sr.	Location	 Permissible Norms	Desired minimum
No.		 [in dB(A)]	thickness of Green Belt
1	Along road	65 (Commercial Area)	20
2	Near CHPs	75	30

F] The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.

Page 5 of 8

# Schedule-III Details of Bank Guarantees

Sr.	Consent	Amt of BG	Submissio	Purpose of BG	Compliance	Validity
No.	(C to E/O/R)	Imposed	n Period		Period	Date
1	R	Rs.5/- Lakhs (Fresh)	15 days	Towards compliance of consent conditions		31.07.2015

Page 6 of 8

## Schedule-IV

## **General Conditions:**

1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not

discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.

Industry should monitor effluent quality, stack emissions and ambient air quality

monthly/quarterly.

- The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to

abide by terms and conditions of this consent.

The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW (MH&TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.

9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for

the preceding year April to March in Form-IV by 30th June of every year.

10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

11) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent (in case of Renewal of consent).

12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act,1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).

13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to

see the day to day compliance of consent condition towards Environment Protection.

14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.

15) Neither storm water nor discharge from other premises shall be allowed to mix with the

effluents from the factory. 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

17) Conditions for D.G. Set

a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by

treating the room acoustically.

Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of

Page 7 of 8

insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.

d) Installation of DG Set must be strictly in compliance with recommendations of DG Set

e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use

f) D.G. Set shall be operated only in case of power failure.

- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel

18) The industry should not cause any nuisance in surrounding area.

19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

20) The applicant shall maintain good housekeeping.

21) The applicant shall bring minimum 33% of the available open land under green coverage/plantation. The applicant shall submit a statement on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end, with the Environment Statement.

22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary

permissions from civic authorities for disposal of solid waste.

23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.

24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.

25) The industry shall submit quarterly statement in respect of industries' obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can be downloaded from MPCB official site).

26) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.

27) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dated. 16.11.2009 as amended.

Specific Conditions

1) Transportation of coal shall be by closed system, Conveyor system wherever possible.

2) The applicant shall comply with the conditions of Environmental Clearance granted by MoEF, GOI.

The applicant shall provide continuous automatic ambient air and micrometeorological monitoring station at location indicated by State Board to be set up and operate at its own cost measure SO2, NOx and particulate matter. These CAAQMS shall also have necessary provision of networking to the Air Quality Monitoring network of MPCB.

4) Coal Washeries shall follow the conditions of the Ministry of Environment & Forests, Government of India's Notification No.Q.15017/13/95-CPW, dated 27th January, 1999 strictly.

----0000-----

Page 8 of 8