MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 /24023515 Website: http://mpcb.gov.in



Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai - 400 022

Date: 0-1/11/2014 E-mail: mpcb@vsnl.net

Real Los Consent No: Format 1.0/BO/CAC CELL/EIC-KP-15741-14/R/CAC- 10200 Red/LSI

M/s. Shree Gurudatt SSK Ltd. To, Gat No 61, Akiwat- Takaliwadi Road, Tal Shirol, District Kolhapur

: Renewal of Consent of Sugar & Co-generation unit under RED category. 1. Consent to operate granted by the Board vide No. BO/JD(WPC)/EiC No. - KP Subject

Ref

-11791 - 13/O/CAC-9456 dated 16.11.2013. 2. Minutes of CAC meeting held on 07.10.2014.

Your application: CR1407000270.

For: Renewal of Consent of Sugar & Co-generation unit under Red category. under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M. H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II & III annexed to this order:

- The consent is granted for a period from 01.08.2014 to 31.07.2015.
- The actual capital investment of the Sugar & Co-gen is Rs. 159.07 Cr. 1. (As per C. A. Certificate submitted by industry) 2.

3.

(As per	C	
	s valid for the manufacture of -	Maximum Quantity in MT/M
The Consent 1	Product / By-Product Name Sugar	9000
Sr. No.	Sugar	3000
$\frac{1}{2}$	Molasses	30,000
\\ \frac{2}{2}	Bagasse	3000
1-1	Press mud	15 MW
5 1	Electricity Generation (Co-Gen)	ndustry shall not exceed 2500 TCD
L	or orushing Capacity of Sugar II	A SA ST CO.

(The cane crushing Capacity of Sugar Industry shall not exceed 2500 TCD)

Conditions under Water (P&CP), 1974 Act for discharge of effluent: 4.

Cond	litions under Wate	r (P&CP), 1974 Act for d Permitted quantity of discharge (CMD)		
no.		discharge (CMD) 293 (Sugar 245 + Co-gen	Cchedule -	On land for irrigation
1.	Trade effluent	48) 48)	As per Schedule -	On land for irrigation
2.	Domestic effluent			Page 1 of 8

..... /I /D /I /77607000

- Standards to be achieved As per Schedule - II As per Schedule - II As per Schedule - II Number of Stack Description of stack
- Conditions under Hazardous Waste (M, H & T M) Rules, 2008 for treatment and disposal of hazardous waste

			2.3	
Z.	114	hoiletas fuel	1	
	1011	9-12	4	2423
0.0	215	1,733		
*	Ξ,	3.00	1:	
1	2	1,000	1	
- Taran	_	ુ⊐		
C .	O.	5. 3"	4	10
(A)		100	a .	
	-	7		1
6.1 2	Æ.	15 6		44
2.5	03	A -	11	23
	S	ે દ	19	
Disposal	-	. Service	91	1
	=	- 7	1	
	v		18	
	\sim	-,-	14	890°
4	-60	5.54	4	
	1		- 1	20
	25		. 1	3 2 3
		er 200 s	-	
		9.4	1	200
			_ 1	
			- 1	200
	161	<i>.</i>	- 3	
\geq	10	`*		
			~ 1	
[4]		$-\mathrm{Kg}/\mathrm{A}$	-1	546
		1		30
	100	Υ.	- 1	100
البي	- 1	_ t	20	
	39			44.
	- 1	7		100
		7,500	ा	- 1
	-		-	100
# . i	7.5			12.
4 P		8.		100
-	3	250	-	
استفا				
	147	\mathbf{v}		1.5
	19.00	\circ		7.5
	36	S	1	
				1.
	12.		of t	1 -
	4	() () () () () () () () () ()	353	100
3.	22			1
		5.175.2		100
	13.3			
	1.0	- 1	-	1 .
			7.	
	4.5	10	10	4
- 1	1		30	
6.3	25	600		1
	9	•	C.	4
22 72	9.2	-	20.0	4
報 ア \		. 11		1
				4
		2.0		
	-2			44
		74 72		.3
2.0		3	380	1
384		1	- 37	
Category Quantity UOM	3.		-3.	1
100		1. 4		4
			-	
. 55				
<u> </u>		-	4	2.
9	30			1.
1 ×	10		3:	115
. F			- 10	- 1
		+	•	1
Tyne of Waste	3		4	1
3 6 6	×	4	J.	9 T
	į,		3	
3.39	3	5	≂	二集
	3	. · · ·	J.	-1
	•	13.3		2.1
ಿತಿಕ		10.00	. 5	. 1
1 1		্ৰ	J	~ P
- 1		1	D.	. 1
			S)	. 1
			7	4
15.0				- 1
15/67				ুৰ
37.0				_1
100		W.E	1	્.ૌ
20	7	100	- 7	- 1
. 25% a.	=1		3	
· -	-	1		
o de	A	400	*	្ន
- L			_	
2.20	SF. INO.			٠,F
35)- 3	7	15.	Th.	N B
	2	13.4		
100		- 2	-5	
		1 6	93	- 1450

7. Non-Hazardous Solid Wastes:

military.	作的特	1 E	A.A.	1. 2. 3	4200	
1	<u>ه</u> -	4,0			76. mar. 1	
	¥(<u>-</u> د	184 2007	de dina	400	111
	≝ ີ	2				
1	יים				9 es	
	1	₫ "-		10 m		
3	: <u>.</u>			1		
ਵ			1		7	1
SC		71.1		15.2		
Disposa	Sale*, ** to	ွဲ		2		
.2	<u>ت</u> .	5 41	المح			
	3	Ξ.	3	, <u>t</u>	3	
	gray.	₹.	Ħ١	∵ >		1
		ਨ .	31			
		∃′:	3		ਤੋਂ∵ਂ	1.
	<u></u>	₩,	Ĕ)	. 0	, ر	
	ુર્જુ ∗	ď.	conditioning	<i>(</i>)	-
		~	<u> </u>	A. West		4.
	\$ 200 m				ATTENTION OF DEC	1
	Arr.	172	1			
3			٠٠,	Ž.	f.	1
5				Wayne.	1.	1
Ţ,	403					
Ξ.	10 T	2 12		10 E	44	.
-		1724				
	3223		12	Mg Ink		
₹		10500 MT/A		-	6.0 ML/A	1
	2	\geq	2		≥ 7.	1
\exists		₽.			4	
	47.	2				4.1
				ra.a.	25	
 >						
IS		2		323		
ΙE		20	4.75		<u>ر</u>	
2		0		1	Υ,	
4 5	•					
	11-27-3	47.4	· Č4		He Sa	
	, i	4.4.5			· S	2.3
	3	Boiler Ash	100		1	
4 6	3 🚎	ିଦ		ļ¤	1	
		⊸∢		10	waste water	•
1 4	3	7	-	田	ૅૅ	Ä
		·=		اس		ă
		~ <u>~</u>	29.7	18	1	⊒
	5	<u> </u>	ينتث	ΙĔ	ಹ	မ
	-			Sludge from	3	treatment
	X;				377 ×	副性
	a			1. 1		
	Z	\$ 25 m				
	3	* 4-			\sim	w.T
Control of Waste Onantity UOM Treatment	7					
		73	# 3x(%)		(4) A (5)	
w 196	W. Same	2		() 数据	18,760	.63

- etc, this consent This Board reserves the right to review. same shall be binding on the industry
 - obtaining, n from exemption s consent should not be construed as exemptic of permission from any other Government agencies.

 For:

 Maharashtt

 Consentation of

For and on behalf of the

64.0	1	145		35	10
. V	2.87	-000	street.	4.90	200
7	L W L	-		200	7
		30		15.	
Drawn On			1	1	J.
	2	100	212	14.	3
	¥1.	*	\sim	1	1
-	4		. \sqsubset	1	1
/ 41	6 1	Ø	, CO	1.4	
\cup :	~	~	3	100	
	щ,	۳,	-	4	
2			-	15.00	
-> 1	ದ	cc.	.0		
	-	\vdash	-	123	
27	O)	Q.	<u> </u>	4 5	1
53	701	ਾਹ	7	4	
	0	v	j u	1	
	ابتا	L	ĮΣ		
			Line.	1	
			150		
	1		10.2	1	٠.
			- 7		ं
	4.5.4	Street			
	: · · · ·	133	1		
اور		4 (1		W.
		1	13	4	
	য	A.	1.7	510	
			1 =	74 - 9	
6.3	0		10	4	
Date	17.06.2014	2	100 20 10	V	୍ଦ୍ର
1				. d .	, di
	9	2	11	717	
	0		٠ ۲	21	
		~	19	310	1
			11.	ol.	
	100	-	10	٧.	Ų.
	1		1	4	\$ 35
-			13	4	
	35,3	-			(a)
*	130		20		
14	7	1	10	911	
	200	10		16-4	
	277566	1		~ 1	٠.
	\sim	207776	2	CF9//7	
- 74	$-\infty$	10	2	<u> </u>	47
1	ľ	1 V	313	U	
	1	10	- I I	- 1	
		T	- 1	~ I	3 :
1		II.C	110	~1 1	
	27	10	- L	9	77
-1	10.00	1	- 1		. ~
	10	T:	1	300	
7	Virginia Co.	-	- 1	1	
	4.5	4	7.1		
		4	1	14. d	è,
200	6.2		(F. 1)	ુ નુ	13
14.		1	- 1		
C.	3 🗅	:1	Ks. 100/-	1	100
	4	₹4.	1	• 1	٠.
<u> </u>	4 V	η.	21	\geq 1	٠.
⊙ , +		* 1 C	⊃ 1	$_{\Box}$	15
	-1.~	ราง	- 31	\circ	
~ ==	~	٠1,	-1	n	
_	32.0	4	7		
100	4.	. T	S	3	्टुः
- 8	-	1	~	\sim	
	9	. 1	- 4		
\approx	Q 1	21	100	,@+:1	
		41	. 1	300	75
\prec		3		143	
<u>ا</u> ا		1	1	1.7	
		_1	- 24		
100	134	33.	110		
O.	_ @	1	5.53		13
O	al :	1			
>	7 4	. 4	4.4		
T. P.	4		~	-	1
2		1	7	- 24	١.
7	.	30	1		1
	~	1	tube .	0.6	1
~ .					
Ž.	23		12.	1.50	
Received Consentitee of			***	-22-	1
ŽĽ			10.00	- 1- 1-6-1	

- MPCB Kolhapur, and Sub -Regional Officer compliance of the consent condition are directed to ensure the Regional Officer
 - Chief Accounts Officer, MPCB, Mumbai.
- desk-for record & website updation purposes က

Schedule-I

- Terms & Conditions for compliance of Water Pollution Control
- 1) As per your application, you have provided Effluent Treatment Plant (ETP)
 - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr.	Parameters	Standards prescribed by Board
No.		Limiting Concentration in mg/l, except for pH'
01	pH	5.5.9.0
∞02	Oil & Grease	10
03.	BOD (3 days 27oC)	100
04	Sulphate	1000.
05	Suspended Solids	100
06	COD	250
-07	Chloride	600
08	Total Dissolved Solids	2100

- Cl The treated effluent 293 CMD shall be disposed on land for irrigation on 10 hector of own land /as per the bilateral agreement with farmers.
- DI CREP conditions for Sugar Factory
 - i. Operation of ETR shall be started at least one month before starting of cane crushing to achieve desired MLSS. So as to meet prescribed standards from day one the operation of mill.
 - ii. Waste water generation shall be maintained as 100 liters per ton of cane
 - iii. Industry shall achieve zero discharge into in land surface water bodies
 - iv. 15 days storage capacity tank shall be provided for treated effluent to take care of no demand for irrigation.
- E] Industry shall maintain properly the arrangement provided for covering the effluent collection system and to avoid the ingress of Bagasse other material.
- FIGURE THE Unit shall operate ETP even after completion of the crushing season so that any effluent generated during washing & maintenance is discharged after proper treatment.
- G] The unit shall optimize water use in industrial process & maintain records of water consumption & waste water generation.
- As per your consent application, you have provided the septic tank & soak pit.
 - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards.
 - (1) Suspended Solids Not to exceed 100 mg/l.
 (2) BOD 3 days 27°C Not to exceed 100 mg/l.
 - C] The treated sewage shall be disposed on land for gardening/irrigation

Page 3

M/s. Shri Gurudatta Sugars Ltd., SRO Kolhapur/I/R/L/77607000

- The industry shall have bilateral agreement with the farmers on whose land the treated effluent is used for irrigation purposes and a copy of the agreements with validity shall be submitted to the Regional/Sub-Regional Office of the Board.
- The industry shall create Environmental Cell by appointing an Environmental Engineer, Chemist and Agriculture expert for looking after day to day activities related to Environment and irrigation field where treated effluent is used for irrigation.

4) CONDITIONS FOR MOLASSES STORAGE:

- (i) The molasses shall be properly collected and stored in steel tanks which shall be leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- (ii) The capacity of tanks for storage of molasses shall be such that it will take care of bumper production of sugar, non-lifting of molasses etc.
- (iii) All the area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- (iv) Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board. Intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- (v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near /on the tank.
- (vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines if applicable.

II) Conditions under Water (Prevention & Control of Pollution) CESS Act, 1977 as amended

The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. No.	Purpose for water consumed	Water consumption quantity (CMD)
1	Industrial Cooling, boiler feed etc.,	250.0
2.	Domestic purpose	60.0
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	600.0
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	

(My

Page 4of 8

Schedule-II

Terms & conditions for compliance of Air Pollution Control

1. As per your application, you have provided the Air pollution control (APC) system and also erected following stack (s) to observe the following fuel pattern-

Sr. No.	Stack Attached to	APC System	Height in meter	Type of Fuel	Quantity	S %	SO ₂ Kg/ Day
1	Boiler (70 TPH)	Wet Scrubber	65	Bagasse	840 MT/D	0.2%	3360
2	Boiler (40 TPH)	Wet Scrubber	65	Bagasse	36 MT/D	0.2%	144
3	D.G. Set (500 KVA)		30	HSD	70 Lits/Hr	1%	33.6
4	D.G. Set (125 KVA)		30				

- 2. The Applicant shall provide ESP/ Bag filter/ Wet scrubber to the Bagasse fired boiler and Dust Collector to Sugar bagging section as an Air Pollution control equipments OR as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

	Not to exceed 100 mg/Nm ³
Particulate matter	Not to exceed 100 mg/Nm
Particiliale matter	I THUL TO CACCED THE TOO MENT THE
I di ticatato ministro	

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

M/s. Shri Gurudatta Sugars Ltd., SRO Kolhapur/l/R/L/77607000

Page 5of 8

Schedule-III Details of Bank Guarantees

Sr. No.	Consent (C to E/O/R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
1	Renewal of Consent	Rs. 9.0 Lacs	To be extended	The industry shall reduce waste water generation to 100 litrs. Per ton of cane crushed.	Monitoring purpose	31.08.2015
2	Renewal of Consent	Rs. 5.0 Lacs	To be extended	O & M for achieving consented standards of Effluent. O & M for achieving consented standards of Stack emission,	30.04.2015	31.08.2015

The V

M/s. Shri Gurudatta Sugars Ltd., SRO Kolhapur/I/R/L/77607000

Page 6of 8

Schedule-IV General Conditions

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) Industry should monitor effluent quality, stack emissions and ambient air quality monthly.
- 3) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 4) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 5) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 6) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 7) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW (MH&TM) Rules 2008, which can be recycled /processed /reused /recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 8) The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M, H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 9) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 10) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- 11) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (www.mpcb.gov.in).
- 12) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 13) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 14) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 15) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 16) Conditions for D.G. Set
- a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting

(Way

Page 7of 8

the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

Industry should make efforts to bring down noise level due to DG set, outside industrial

premises, within ambient noise requirements by proper sitting and control measures.

Installation of DG Set must be strictly in compliance with recommendations of DG Set

A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.

D.G. Set shall be operated only in case of power failure. f)

- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. g)
- The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit h) for generator sets run with diesel.

17) The industry should not cause any nuisance in surrounding area.

18) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

19) The applicant shall maintain good housekeeping.

20) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.

21) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary

permissions from civic authorities for disposal of solid waste.

22) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.

23) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain

clean and safe environment in and around the factory premises.

24) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).

25) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.


26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

27) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.

28) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of

the operation thereof.

----0000-----



Page 8of 8