#### MAHARASHTRA POLLUTION CONTROL BOARD

4010437/4020781 Phone:

/4037124/4035273

24044532/4024068 /4023516 Fax

Email enquiry@mpcb.gov.in

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near

Sion Circle, Sion (E), Mumbai - 400 022

Consent order No :- Formate 1.0 / BO/CAC-Ceil EIC No MU-6063-14/21st CAC / 1976 Date- 15/12/2014

M/s.Johnson & Johnson Ltd;

LBS Marg, Mulund (W), Mumbai - 400 080

Subject: Amendment in Existing Consent to Operate Red category.

:1.Existing consent granted vide letter MPCBHQ/JDno

PAMS/Mumbai/R/CAC-186 dated 19.01.2012 which is valid upto 30.06.2016

2. Minutes of CAC meeting held on 28.11.2014

Your application: CO1407000128

Dated: 20.06.2014

For: Amendment in Existing Consent to Operate

under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, IN & IV annexed to this order:

- 1. The consent is granted for a period from date of issue of consent upto 30.06.2016.
- 2. The actual capital investment of the industry is Rs.181.97 Crs. (As per C.A.Certificate submitted by industry).

3. The Consent is valid for the manufacture of -

Sr. No.	Product / By-Product Name	Maximum Quantity MT/M
1	Pressure Sensitive Adhesive Tapes	1100.00
2	Gauze & Bandages	700.00
3	Baby Powder Prickly Heat Powder	1400.00
4	Miscellaneous Baby Products	160.00
5	Gynatic & Therapautic Products (Sanitary Napkins)	1400.00

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Jiiuiu	ons under water (1 &C1	), 1314 ACC 101	uischarge of	emuent.
Sr.	Description	Permitted	Standards	Disposal
no.		quantity of	to be	
		discharge (CMD)	achieved	
1.	Trade effluent	100	As per Schedule – I	70 % used on land for gardening and remaining discharged
2.	Domestic effluent	80	As per Schedule – I	in MCGM drainage line.

M/s Johnson & Johnson Ltd SROMumbailV/I/R/L/00240000

Page 1 of 10

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr.	Description of stack /	Number of Stack	Standards to be achieved
1	Boilers (2 nos)	1	As per Schedule -II
2	Thermopac		
3	DG set (750, 500, 250, 125 X 2nos	5	As per Schedule -II

6. Conditions about Non Hazardous Wastes:

Sr.	Type Of Waste	Quantity &	Treatment	Disposal
no.		Kg/A		
1	Recycleable	9,00,000 Kg/A		Recycled through
	waste(Talc/Perfume			authorised
	Jars, Wooden			recycler
	Pallets, Shippers,			
	Boxes, Metal Waste			
	& Tree Leaves			7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
2	Landfill waste	20000 Kg/A	<u> </u>	Landfill
	(Talc Perfume Jars,			
	Wooden Pellets,		W. C.	
	Sanitary Napkin,			
	Paper			
	cartons/boxes,			
	Metal waste, cloth			
	trimmings, tree	* (		
	trimmimgs etc)			3.6
3	Canteen Waste Wet	96000 Kg/A	<u> </u>	Manure
	Recyclable	25000 Kg/A		Reuse
	shredded waste			
4	Canteen Waste Dry	12000 Kg/A		Landfiill

7. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste.

	Sr. Type Of Waste Category Quantity UOM Treatment Disposal					
Sr.	Type Of Waste	Category		UOM	Treatment	Disposal
No.			Kg/D			
1	Oil-containing	3.1	5	Kg/D		CHWTSDF
	cargo residue,					
	washing water					
	and sludge					
2	Wastes/residue	5.2	4	Kg/D	<del></del>	CHWTSDF
	containing oil					
3	Discarded	15.2	6	Kg/D		CHWTSDF
	asbestos					
4	Contaminated	20.1	5	Kg/D	_	CHWTSDF
	aromatic, aliphatic					
	or napthenic					
	solvents					
5	Wastes and	21.1	10	Kg/D	<u> </u>	CHWTSDF
	residues					
6	Fillers residues	21.2	2	Kg/D		CHWTSDF
7	Wastes/residues	23.1	5	Kg/D		CHWTSDF
	(not made with					
	vegetable or					

M/s Johnson & Johnson Ltd SROMumbailV/I/R/L/00240000

( Jut-

Page 2 of 10

	animal mate					
8	Spent solvents	20.2	5	Kg/D		CHWTSDF
9	Chemical- containing residue from decontamination and d	33.1	2	Kg/D		CHWTSDF
10	Sludge from treatment of waste water	33.2	5	Kg/D		CHWTSDF
11	Discarded containers / barrels / liners	33.3	5	Kg/D	_	CHWTSDF
12	Flue gas cleaning residue*	34.1	3.5	Kg/D		CHWTSDF
13	Toxic metal- containing residue from water purification	34.2	3	Kg/D		CHWTSDF
14	Chemical sludge, oil and grease skimming residues	34.4	45	Kg/D		CHWTSDF
15	Sludge and filters contaminated with oil	3.3	10	Kg/D		CHWTSDF
16	Used /spent oil	5.1	2	Kg/D		CHWTSDF
17	Date -expired, discarded and off specification drugs/Medicines	28.3	40	Kg/D		CHWTSDF
18	Spent organic solvents	28.5	55	Kg/D		CHWTSDF

8. The Board reserves the right to review, amend, suspend, revoke etc. this consent

and the same shall be binding on the industry.

9. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities as well as local Body.

10. This consent is issued by overriding consent no MPCBHQ/JD-PAMS/Mumbai/R/CAC-186 dated 19.01.2012.

For and on behalf of the Maharashtra Pollution Control Board

> Mital, LAS er Secretary

Received Consent fee of -

Sr.	Amount(Rs.)	DD. No.	Date	Drawn On
No.				
1.	563123	817333	11.06.2014	Citi Bank
	Previous conser	nt fees		
1.	513000	669155	20.05.2011	HDFC Bank
2.	1035000	681518	16.12.2011	HSBC

Copy to:

- MPCB, conditions. 1. Regional Officer -Mumbai and Sub-Regional Officer-Mumbai-IV MPCB, - They are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updation purposes.

M/s Johnson & Johnson Ltd SROMumbailV/I/R/L/00240000

Page 4 of 10

# Schedule-I

# Terms & conditions for compliance of Water Pollution Control:

- 1) A] As per your application, you have provided the combined Effluent Treatment Plant (ETP) for treatment of domestic and trade effluent with the design capacity of 300 CMD.
  - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr No	. Parameters	Standards prescribed by Board (If any)
		Limiting Concentration in on the mg/l, except for pH
01	pН	6.0-8.5
02	Oil & Grease	10
03	BOD (3 days 27oC)	100
04	Total Dissolved Solids	2100
05	Detergents	2
06	Suspended Solids	100
07	COD	250
08	Phenolic Compound	4
09	Sulphate	1000
10	Chlorides	600
11	Copper	3.0
12	Lead	0.1
13	Sulphide	1.0
14	Phosphate	5
15	Arsenic	0.2

- C ) The treated effluent shall be disposed on land for gardening approx 105 CMD and remaining shall be discharged to Municipal sewer.
- 2) A.] As per your consent application, the domestic effluent is treated in ETP
  - B] In case the treatment system is combined for trade effluent and sewage then the standards and disposal path prescribed at sr. no.1 B & C of schedule I shall be applicable.
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or/and extension or addition thereto.

Put

Page 5 of 10

4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained

in the said act.

Sr.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	20
2.	Domestic purpose	100
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	120
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	00

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act,1986 and rule made there under from time to time/Environmental Clearance / CREP guidelines.

Page 6 of 10

#### Schedule-II

### Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached To	APC System	Height in Mtrs.	Type of Fuel	Quantity & UoM	S %	SO <sub>2</sub> Kg/Day
1	Boiler (2 Nos)	stack	30.5	Natural Gas	1200 KL/D	<b></b>	
2	Thermopac (Stand-by)	Stack		FO	1.8 T/D	4.5	162
3	D.G.Set (750 KVA)	Stack	8	HSD	100 Lit/Hr	$\sum_{i=1}^{N}$	48
4	D.G.Sets 500 KVA)	Stack	8		400 Liv/Hr	1	192
5	D.G.Sets 125 KVA)	Stack	8		25 Lit/Hr	1	12
6	D.G.Sets (125 KVA)	Stack	8		25 Lit/Hr	1	12
7	D.G.Sets (250 KVA)	Stack	7.5		50 Lit/Hr	1	24

- 2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and sule made there under from time to time / Environmental Clearance / CREP guidelines.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate Not to exceed	150 mg/Nm <sup>3</sup> .
matter	

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacementalteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

W jut

# Schedule-III Details of Bank Guarantees

Sr. No.	Consent (C to E/O/R)	Amt of BG Imposed	Submissi on Period	Purpose of BG	Complian ce Period	Validity Date
1	C to R	Rs 5	Within 15 days from the date of issue of consent	O & M of PCS	30.06.2016	30.10.2016

MAN ASTITUTE ON THE CONTROL OF THE C

M/s Johnson & Johnson Ltd SROMumbailV/I/R/L/00240000

Page 8 of 10

# Schedule-IV

#### **General Conditions**

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 3) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 4) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 5) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 6) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 7) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled
- 8) /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30<sup>th</sup> June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(<a href="www.mpcb.gov.in">www.mpcb.gov.in</a>).
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

White

M/s Johnson & Johnson Ltd SROMumbailV/I/R/L/00240000

Page 9 of 10

- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set
  - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
  - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
  - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
  - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
  - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
  - f) D.G. Set shall be operated only in case of power failure.
  - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
  - h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a statement on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end, with the Environment Statement.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt.d 16.11.2009 as amended.

----0000-----

Page 10 of 10