MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 /24023515 Website: http://mpcb.gov.in E-mail: mpcb@vsnl.net



Kalpataru Point, 2nd - 4th Floor, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai - 400 022

RED/LSI

Ref

Date: 29/12/2014

Consent No : Format 1.0/BO/JD(WPC)/EIC No. AD-15878-14/R/CC-12488

To. M/s. Tata Chemicals Ltd., D-1,MIDC Krushnoor,Tal-Naigaon, Dist-Nanded 431709

Subject: Consent to Renewal under RED Category.

: 1. Earlier consent to Operate granted videNo.BO/JD(WPC)/ROABAD/EIC-AD 12539-12/O/CC-4644 ,Dated 30.05.2013

2. Minutes of Consent Committee meeting held on 12.12.2014.

Your application CR1409000539 dated 30.08.2014.

For: Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- The consent is granted for a period from: 01.09.2014 to 31.08.2015.
- The actual capital investment of the industry is Rs. 54.04 Crore. (As per C.A. Certificate submitted by industry)
- The Consent is valid for the manufacture of -

he Con Sr.	Product / By-Product Name	Maximum Quantity & UoM
No.	(PS)	2700 KL/Month
1.	Rectified Spirit (R.S.)	2 KL/Month
2.	Fusel Oil	2 MW
3.	Captive Power	350 MT/Month
4. 5.	Compost WPB(Bulb)	during rainy season i.e. from 10 th June

(The distillery should remain closed during rainy season i.e. from $10^{
m th}$ June to 10th September every year)

Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr.	Description	Permitted quantity of	be achieved	Disposal
no. 1.	Trade effluent	discharge CMD) 176.00	As per Schedule –I	Bio- Composting
2.	Domestic effluent	20.00	As per Schedule -I	On land for irrigation

M/s. Tata Chemicals ltd., SRO Nanded I/R/L/14212000

Page 1/8

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr.	Description of stack /	Number of Stack	Standards to be
no.	source		achieved
1.	Boiler	I	As per Schedule -II
2.	DG Set	I	As per Schedule -II

6. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr. No.	Type Of Waste	Category	Quantity	UOM	Disposal
1.	Used/Spent Oil	5.1	1.00	MT/Y	Mixed with bagasse and used as fuel in own Boiler
2.	Chemical Sludge ,oil & grease skimming residues	34.4	1.60	MT/Y	Mixed with bagasse and used as fuel in own Boiler

Non-Hazardous Solid Wastes

Sr.	Type of Waste	Quantity	UOM	Treatment Disposal
No.				
1	Boiler Ash	50	MT/D	Sale to Brick
				Mauufacturer

- 7. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry
- 8. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.
- 9. Industry shall not start production activity without prior permission from Board.

For and on behalf of the Maharashtra Pollution Control Board

(Rajeev Kumar Mital, IAS)

Member Secretary

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1.	1,00,000/-	001127	30.08.2010	HDFC Bank

Copy to:

- Regional Officer Aurangabad and Sub-Regional Officer Nanded.
 They are directed to ensure the compliance of the consent conditions & to carry out monthly monitoring of pollution control system.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updation purposes.

M/s. Tata Chemicals ltd., SRO Nanded I/R/L/14212000

Page 2/8

Schedule-I

Terms & conditions for compliance of Water Pollution Control:

1) A] As per your application, you have installed the Effluent Treatment Plant (ETP) with the design capacity of 176 CMD.

B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr. Parameters No.	Standards prescribed by Board		
	Limiting Concentration in mg/l, except for pH		
01 pH	5.5-9.0		
02 Oil & Grease	10		
03 BOD (3 days 27oC)	100		
04 Sulphate	1000		
05 Suspended Solids	1000		
06 COD			
07 Chloride	250		

C] The treated effluent other than spent wash shall be used on land for gardening within factory premises only. In no case, at any time effluent shall find its way to any other water body directly or indirectly

D] Conditions for Aerobic Composting:

- i. The spent wash should be stored in impervious tanks. The spent wash tanks should have proper lining with HDPE and should be kept in proper condition to prevent ground water pollution. As per the CPCB recommendation and undertaking given by the company, storage should not exceed 30 days capacity.
- ii. Applicant shall ensure availability of adequate filler material such as press mud, bagasses, agricultural, biological waste as required for effective composting system.
- iii. Composted material shall meet the following specifications-

 Moisture
 ... 30 to 35%

 C/N
 ... Below 17

 Nitrogen
 ... 1.5 to 2%

 Phosphorous
 ... 1.5 to 2%

 Potassium
 ... 3 to 4%

- iv. The composting site shall be prepared as per the guideline enclosed. Composting shall be such that it includes mechanical mixing and spraying of spent wash along with mechanical aeration to ensure thorough composting. Hand/manual spraying of spent wash shall not be permitted.
- v. The compost leachete (1 gr. of compost mixed with 100 ml. of distilled water and filtered) Filterate shall conform to the following limit.

BOD 3 days 27 Deg. C. Setween 7.5 to 8.0 Not to exceed 30 mg/l

vi. A pucca leak proof guard pond of 30 days holding capacity as per (i) above shall cope up with the effluent discharge during short term process disturbances In case of prolonged disturbance in effluent treatment and disposal system, distillery shall be shut down and shall not be restarted without rectifying the system.

M/s. Tata Chemicals ltd., SRO Nanded I/R/L/14212000

Page 3/8

- vii. The composting site/pits shall be made leak proof by proper lining. A catch drain shall be provided around the composting site to collect the storage pound for application on compost depots. Arrangements for overturning of compost material in windrows and spraying of spent wash shall be made to ensure appropriate aeration and uniform distribution of spent wash.
- viii. In case of composting in open fields, the application of spent wash shall stop by end of April, so that compost is ready and the site is cleared of the composted manure before monsoon (i.e. 31st May). The manure shall be collected and stored on a raised platform with suitable rain cover so that the compost manure is not washed away by rain/runoff.
- ix. Characteristic of soil, ground water and effect on crop yield should be monitored in the area where compost is used as manure and results thereof shall be compiled and reported in the Environment statement to be submitted every year.
- x. The test wells shall be provided around the compost site for ground water monitoring. The well water quality has to be maintained at 2006 level.
- xi. Top pullover impervious sheets shall be provided for entire compost yard, press mud and compost storage so as to cover the same during untimely rains and idles period.
- xii. The operation of distillery should be restricted to 270 days in a year and that it will not operate during rainy season.
- 1) The Industry shall create Environment Cell By appointing an Environmental Engineer, Chemist and Agriculture expert for looking after day to day activities related to Environment and irrigation field where treated effluent is used for irrigation.
- 2) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines if applicable.

II) Conditions under Water (Prevention & Control of Pollution) CESS Act, 1977 as amended

The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	
2.	Domestic purpose	30.00
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	635.00
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	

W jut

Page 4/8

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached to	APC System	Height in meters	Type of Fuel	Quantity & UoM	S%	SO ₂ Kg/ Day
1	Boiler	ESP	40	Bagasse	250 MT/day	0.2	1000

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance guidelines.

3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	150 mg/Nm ³ .
T di bionidio		

4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution control equipment.

5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of

any control equipment, other in whole or in part is necessary).

M/s. Tata Chemicals ltd., SRO Nanded I/R/L/14212000

Page 5/8

Schedule-III

Specific Conditions of Bank Guarantee & time Bound Programme

Sr. No.	Consent (C to E/O/R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
L.	Consent to Renewal	Five Lacs	Within 15 days	Towards O & M of pollution control system.	31.08.2015	31.12.2015

					S. Carlotte and Ca	
						,

M/s. Tata Chemicals ltd., SRO Nanded I/R/L/14212000

Page 6/8

Schedule-IV

General Conditions:

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- 3) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 4) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 5) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 6) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 7) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled
- 8) /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazarsous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent (in case of Renewal of consent).
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act,1981 and Environmental Protection Act,1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 13) The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Wastes (M,H &TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

M/s. Tata Chemicals Itd., SRO Nanded I/R/L/14212000

= Page 7/8

- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set
 - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
 - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
 - f) D.G. Set shall be operated only in case of power failure.
 - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
 - h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 26) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 27) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

----0000-----

M/s. Tata Chemicals ltd., SRO Nanded I/R/L/14212000