

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781  
/4037124/4035273  
Fax : 24044532/4024068  
/4023516  
Email : enquiry@mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga  
Scheme Road No. 8, Opp. Cine Planet Cinema,  
Near Sion Circle, Sion (E),

Mumbai - 400 022

Red/S.S.I

Date: 08 /Jan/2015

Consent No: BO/AS (T)/R/EIC NO.NM-5207-14/CC- 293

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

.....  
CONSENT is hereby granted to

M/s. Jyoti Dye Chem Pvt. Ltd.,  
D-76/1, MIDC, Turbhe,  
TTC Industrial Area,  
Navi Mumbai

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.10.2015
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Dyes & Dyes Intermediates	7	MT/M
2	Organic Chemicals	7	MT/M

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 4.00M<sup>3</sup>.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 0.40M<sup>3</sup>.
- (iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
2	BOD 3 days 27 deg C	Not to exceed	100 mg/l
3	Oil & Grease	Not to exceed	10 mg/l
4	Suspended Solids	Not to exceed	100 mg/l.
5	COD	Not to exceed	250 mg/l.
6	TDS	Not to exceed	2100 mg/l

(iv) **Trade Effluent Disposal:** The treated effluent should be recycled to the maximum extent and remaining treated effluent should be sent to CETP.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- |                       |               |     |       |
|-----------------------|---------------|-----|-------|
| (1) Suspended Solids  | Not to exceed | 100 | mg/l. |
| (2) BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:** NIL

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

**4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

- |   |     |       |     |
|---|-----|-------|-----|
| (i) Domestic purpose  | ... | 2.00  | CMD |
| (ii) Water gets Polluted & Pollutants are Biodegradable             | ... | 5.0   | CMD |
| (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic | ... | 0.00  | CMD |
| (iv) Industrial Cooling, spraying in mine pits or boiler feed       | ... | 5.00  | CMD |
| (v) Agricultural / Gardening  | ... | 00.00 | CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

**5. CONDITIONS UNDER AIR ACT :**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**a. Control Equipment:**

- I. Adequate fume extraction system shall be provided to limit the emissions.
- II. There shall not be any secondary (fugitive) emissions.

**b. Standards for Emissions of Air Pollutants:**

- |                      |               |                          |
|----------------------|---------------|--------------------------|
| (i) SPM/TPM          | Not to exceed | 150.0 mg/Nm <sup>3</sup> |
| (ii) SO <sub>2</sub> | Not to exceed | 62.64 Kg/day.            |
| (iii) HCL            | Not to exceed | 35 ppm                   |

- (ii) **The applicant shall observe the following fuel pattern:-**

Sr. No.	Type Of Fuel	Quantity	UOM
01	LDO	75.50	Lit/Hr

- (iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	APCS provided	Height in Mtrs.
1	Boiler	Stack	18.00
2	Reactor	Alkali Scrubber	10.00

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) **Other Conditions:**
- 1) The industry should not cause any nuisance in surrounding area.
  - 2) The industry should monitor stack emissions and ambient air quality Regularly.

#### 6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- g. D.G. Set shall be operated only in case of power failure.
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
09. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
10. If CETP does not operate efficiently and problem of pollution occurs, industry should voluntarily stop the production or total effluent should reuse.
11. Industry shall re-start production activity after obtaining written permission of Regional Officer about operational status of pollution Control systems.
12. Industry shall submit the Bank Guarantee of Rs.1.0 Lakhs within 15 days to Regional Office, MPC Board, Navi Mumbai towards operation and maintenance of pollution control systems and compliance of condition no. 11 above.
13. The capital investment of the industry is Rs 37.5 Lakh as per C A Certificate submitted by Industry.

  
(P. K. Mirashe)

Assistant Secretary (Technical)

To,  
M/s. Jyoti Dye Chem Pvt. Ltd.,  
D-76/1, MIDC, Turbhe,  
TTC Industrial Area,  
Navi Mumbai

Copy to :

RO, Navi Mumbai / SRO, Navi Mumbai I. -- They are directed to ensure the compliance of consent conditions.

CAO/Cess Branch/Master file.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	36,000/-	010535	05.10.2011	Vijaya bank