# MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 40

4010437/4020781

/4037124/4035273

Fax:

24044532/4024068

/4023516

Email:

enquiry@mpcb.gov.in

Visit At: http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion-Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E).

Mumbai - 400 022

Consent order No: - Formate 1.0/BO/CAC-Cell/EIC No NG-12003-14/29th CAC/4253

Date-15/04/2015

To, M/s Gharda Chemicals Ltd., Plot No. B-22 to 24, 27 to 29 & A- 81 to 83, MIDC, Ph-I, Dombivli.

Subject: Renewal of Consent to operate and amendment in consent for change in product-mix under RED category

Ref: 1. Earlier Consent granted vide No Formate 1.0/BO/CAC-Cell/EIC No KN-6602-14/4th CAC/CAC-4706 dated 19.05.2014

2. Your application approved in CAC meeting held on 25.03.2015.

Your application: CR1411000483

Dated:10.11.2014

For: Renewal of Consent to operate and amendment in consent for change in

product-mix.

under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

1. The consent is granted for a period from date of issue of consent upto 31.07.2019.

2. The capital investment of the industry is Rs. 145.26 Crs. (As per CA's certificate submitted by an industry).

3. The Consent is valid for the manufacture of -

r. Io.	Product Names	Maximum Quantity in MT/A;
- management a comm	Oxyclozanide (Condensation & Purification)	120
	OR	
	Sulfosulfuran*	36
	OR	
	Acetamipride*	72
	OR	
	Rafoxanide	96
	OR	
	Mepiquat Chlori-le	120
	OR	
	Cypermethrin*/Alphamethrin*/Lamda Cyhalothrin	120
	Isoproturon*	4800
	OR	

	Bispyribac Sodium*/Cypermethrin*/Alphamethrin*/ Lamda Cyhalothrin *	4164
3	Cypermethric Acid/ Cypermethric Acid Chloride	2400 (660 for captive use in Cypermethrin)
	OR	
	Cypermethric Acid/ Cypermethric Acid Chloride	600
	And	&
	Vanillin Technical	6000
	OR	
	Cypermethric Acid/ Cypermethric Acid Chloride	960
	And	&
	Pigment Red	1200
4	Clodinofop Propargyl (CDFP)*	72
	OR	
	Cypermethrin*/ Alphamethrin*/ Lambda Cyhalothrin*	72
5	Diflubenzuron*	96
	OR	
	Cypermethrin*/ Alphamethrin*/ Lambda Cyhalothrin*	48***
	And	
	Chloro Hydroxy Benzo Phenone (CHBP)/ Poly Ether	312
	Ketone - PEK/PEKK/Poly Ether Imide (PEI) its	
	monomer & Polymer	
	OR	
	ABPBI	108
	And	+
	DPSO2	120
	And	
	PTC	180
6	Fipronil*	444
	OR	
	Cypermethrin*/Alphamethrin*/Lambda Cyhalothrin*	444
7	R&D Activities	••
8	Insecticide Formulations#	3000

Note: (\*) Product along with its formulation

(#) Formulations from own technical products or by procuring technical products from outside.

List of By-Products

Sr No	. By Product Names	Maximum Quantity
1	Spent Acid	6840 MT/A
$\overline{2}$	Ortho Nitro Cumene	1956 MT/A
	OR	
	Ortho Cumidine	1008 MT/A
3	Sodium Salt of Methane Sulfinic Acid	648 MT/A
	Oi!	33.6 KL/ A
4	Cupric Chloride Solution	204 KL/A
 5	Solution	

	OR	
	Sodium Sulphite / Sodium Resulphite Solution	14040 KL/ A
i	and	
	Compressed Sulphur Diskide gas	1080 MT/A
	Market Commence of the Commenc	integral No. 1
17	Liq. Ammonia	JUSU NIVA PILIFA
3	Aluminum Chloride Solution (From CHRF Frocess)	6728.4 MT/A
	ÛR	
i	Sodium Sulphite / Sodium Bisulphite Solution	612 MT/A
	AND	
1	HCL Solution from ABPBI process	504 MT/A
9	Spent HCl Solution	232.8 MT/A
10	Spent Dimethyl Amine	900 MT/A

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr.	Description	Permitted quantity of	Standards to be achieved	Disposal
. no.		discharge (CMD)	be acmeved	
1.	Trade effluent	525	As per Schedule	CETP
2.	Domestic effluent	95	As per Schedule	CETP

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

and the second	* Description of stack / * source		The state of the s
1.	Boiler {2 Nos. – One is coal fired & another oil fired (standby)}	1	As per Schedule –II
2.	Process vents from Scrubbers	5	As per Schedule –II
3.	DG set	4	As per Schedule –II

6. Conditions under Non hazardous Wastes

Sr.	Type of waste	Quantity	Treatm	Disposal
no.			ent	
1	Metallic scrap	840 Kg/day		Sale
2	Waste Insulation material	30 Kg/day		Sale to Recycle
3	Civil Debris	330 Kg/day		Land filling
4	Stationary paper waste	160 Kg/day		Incineration/ Sale to recycle
5	Non Metallic scrap	30 Kg/day		Sale
6	Boiler Ash	21.8 Mt/day		Sale to cement/brick manufacturer

7. Conditions under 1) Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste. :

Sr. No.	Type Of Waste	Category	Quantity	UOM	Treatmen	t Disposal
1	Contaminated aromatic, aliphatic or napthenic solvents not fit for originally intended use.	20.1	1000	МТ/А		Incineration at their Lote unit/Sale as a by-product.
2	Distillation residue	20.3	80	MT/A		Incineration at Lote
3	Chemical sludge including calcium sulfate from Waste Water Treatment	29.2	2200	MT/A		Sent to CHWTSDF
4	Discarded containers / barrels.	33.3	3000	Nos./A		Sale to party after decontaminatio n.
5	Contaminated Cotton waste	5.2	4.8	MT/A		Incineration at Lote
6	Contaminated Saw Dust	29.1	4.8	MT/A		Incineration at Lote
7	Date expired and off specifications pesticides	29.3	10	MT/A		Incineration at Lote
8	Used / spent oil	5.1	7.5	MT/A		Incineration at Lote / Sale as by-product
9	Spent activated carbon	28.2	48	MT/A		Incineration at Lote / Sale as by-product
10	Electronic wastes	Schedule IV	1.5	MT/A		Sent to MPCB/CPCB authorized recycler

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. This consent should not be construed as exemption from obtaining necessary NOC / permission from any other Government authorities.
- 10. This consent is issued in accordance with MoEF, Govt of India circular dated December 14, 2006 stating that in cases of change of product-mix, changes in the quantities or the numbers of product may be allowed without E.C by the concerned SPCB provided such changes in the quantities of product are in the same category and are with the previously granted overall total limits.
- it. Industry, the by product generator, should ensure that all the vehicles used to transport by-product to the vendor industry to be fitted with web based GPS system to record the origin to destination position and shall self monitor the compliance and submit name this report to the Board.

- 12. Industry shall obtain affidavit from vendors stating that the by-product purchased from PP is used as raw material in their respective industries.
- 13. Industry shall submit BG of Rs. 2 lakh towards compliance point no. 11 & 12 above.

For and on behalf of the Maharashtra Pollution Control Board

(Dr. P. Anbalagan, IAS) Member Secretary

Received Consent form fee of -

M/s Gharda Chemicals Ltd SRGKalvani/1/R/L/55/2009/0000

Sr. No.	Amount(Rs.)	DD. No.		Drawn On
1	Rs 14,52,775	467973	29/10/14	Canara Bank

The balance fees of Rs 121050/- shall be considered at the time of next renewal of consent.

### Copy to:

- 1. Regional Officer Kalyan and Sub-Regional Officer- Kalyan 1, Chief Accounts Officer, MPCB, Mumbai.
- 2. CC/CAC desk- for record & website updation purposes.

#### Schedule-I

# Terms & conditions for compliance of Water Pollution Control:

1) Al As per your application, you have provided the combined Effluent Treatment Plant (ETP) with the design capacity of 620 CMD.

B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time,

whichever is stringent.

Sr.No	Parameters	Standards prescribed by Board (If any)
		Limiting Concentration in mg/l, except for pH
01	рН	5.5 to 9.0
02	Oil & Grease	10.0
03	BOD (3 days 27°C)	100
04	COD	250
05	SS	100
06	CN	0.2
07	Phenol	1.0
08	Pesticides	Shall be Nil
09	TAN	50.0
10	Copper	3.0

- C] The treated effluent shall be discharged to the CETP 620 CMD
- 2) A.] As per your consent application, the domestic effluent is treated in ETP.
  - B] In case the treatment system is combined for trade effluent and sewage then the standards and disposal path prescribed at sr. no.1 B & C of schedule I shall be applicable.
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or/ and extension or addition thereto.
- 4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

ाक्षाचीव Chemicals Lid SROKalyanI/I/R/I/S9629000

Vage noti?

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	645.0
2.	Domestic purpose	100.0
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	400.0
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	
5	Agriculture / Gardening	30

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.

M/s Gharda Chemicals Ltd SROKelyant/1/R/Leven 1999.

H 2 Par Lugar Capaci

### Schedule-II

#### Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC) system and erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached To	APC System	Height in Mtrs.	Type of Fuel	Quantity	S %	SO <sub>2</sub> Kg/Day
1	Steam Boiler-	ESP &	58	Coal	54.5	<	Coal-
	2 Nos., 1. Coal	Dust	(Combin	(Imported	MT/day of	than	1635
	fired &	collection	ed)	or	coal /OR 22	1.5 %	<u> </u>
	2. Oil fired	system,		indigenou	T/day of		FO-
	(Standby)	adequate		s)/ OR	Furnace oil	coal/	1980
ı		high		FO		< 3 %	
		stack is				in FO	
	DG Set 1250	provided Acoustic	10.0	HSD	0.95 T/Hr.	< 1%	456
2	KVA	Acoustic enclosur	12.8	нар	0.95 T/Hr. (In case of	< 1%	496
	KVA	enclosur			power		İ
3	DG Set 1000	Acoustic	11.8	HSD	failure)		
"	KVA	enclosur	11.0	1100	idilais)		
ļ		e					
4	DG Set 1000	Acoustic	11.8	HSD			
	KVA	enclosur		i Maria Para			
		е					
5	DG Set 1000	Acoustic	11.8	HSD			
	KVA	enclosur					
		е					
	ess Vents				T		
1	CMAC/CMA		26		NA	NA	NA
	Filling Point						
	(Plant 3)						
				To see the second			
2	Process Vents	Scrubber	20.5	NA,	NA	NA	NA
4	Plant 1	s are	20.0	Electricit	11/21	17/1	7477
3	Process Vents	provided	37	y driven	NA	NA	NA
,	Plant 2	pro . raou					****
4	Process Vents	1	26	<del>!</del>	NA	NA	NA
	Plant 3		_ = 0				
5	Process Vents		15.5		NA	NA	NA
	(CMN						
	process) in			Andrews Andrews			
	ETP						

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines. (Concern section shall mention specific control equipments)

3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following

standards:

Particulate	Not to exceed	150 mg/Nm <sup>3</sup>
matter		
HCl	Not to exceed	35 ppm
$Cl_2$	Not to exceed	3 ppm
$H_2S$	Not to exceed	10 ppm
NH <sub>3</sub>	Not to exceed	50 ppm
NO <sub>x</sub>	Not to exceed	50 ppm

4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.

5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

17, Granda Chemicals Ltd SROKulyaniyiyii/159629000 -

Page 2 of 12

# Schedule-III

# Details of Bank Guarantees

CTOR Rs 5.0 Submitted Control Equipments  2 CTOR Rs 2 lakh    CTOR Rs 2 lakh   Control Equipments	Sr. No	Consent (C to E/O/R)	Amt of BG Impose d	Submission Period	Purpose of BG	Complian ce Period	Validity Date
days from the date of issue of consent    CTOR   Rs   2   days from the date of issue of consent   product generator, should ensure that all the vehicles used to transport byproduct to the vendor industry to be fitted with web based GPS system to record the origin to destination position and shall self monitor the compliance and submit monthly report to the Board.    Also industry shall obtain affidavit from vendors stating that the by-product purchased from PP is used as raw material in their respective	1	C TO R	1	Submitted	O&M of Pollution Control Equipments	31.07.2019	
TIL CONTROL	2	C TO R	} =	days from the date of issue of	product generator, should ensure that all the vehicles used to transport byproduct to the vendor industry to be fitted with web based GPS system to record the origin to destination position and shall self monitor the compliance and submit monthly report to the Board.  Also industry shall obtain affidavit from vendors stating that the by-product purchased from PP is used as raw material in their		30.11.2019

#### Schedule-IV

General Conditions:

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- 3) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 5) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW (MH&TM) Rules 2008, which can be recycled /processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30<sup>th</sup> June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent (in case of Renewal of consent).
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.

Page 11 of 12

🍧 ri la Chersicals 134 St#tKalyar1/1/R7L/59629000

- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set
  - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
  - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
  - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
  - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
  - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
  - f) D.G. Set shall be operated only in case of power failure.
  - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
  - h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/plantation. The applicant shall submit a statement on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end, with the Environment Statement.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India. Notification dtd. 16.11.2009 as amended.