SERVA PENNUNDO COMUNER, ICARD

्री इतिहासका **अवस्थितः** । स्थानुः साम् । १८७



graphical for the contract of the factors.

vanadrai - gilii U.L.

EWLM

Committee something to

22/04/2015 Change Not From 3 1 C/RO/CAC-CHI/EIC-PN-22163-14/R/CAC-4595

M/s. Vitthal Corporation Ltd. A/p-Mhaisgaon, Tal-Madha, Dist-Solapur

Subject: I' Consent to Operate for Co-generation unit alongwith amalgamation of Renewal of Sugar unit under RED category.

Ref

- : 1. Consent to operate for sugar unit granted vide No. BO/JDWPC/EIC-PN-15564-13/O/CAC-1265 dated 06.02.2014.
- 2. Consent to Establish for Co-generation plant granted vide No. MPCB/PCI-III/ EIC-PN-2822-09/CC-73 dated 30.07.2009.
- 3. Minutes of CAC meeting held on 07.10 2014 & 10.03.2015.

Your application: CR 1407000336

Dated: 16.07.2014

For: 1st Consent to Operate for Co-generation unit alongwith amalgamation of Renewal of Sugar unit under RED category, under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

The consent is granted for a period up to 31.07.2015. 1.

The total capital investment of the industry is Rs. 110.65 Cr. 2. (As per C. A. Certificate submitted by industry)

valid for the manufacture of 3.

The Consei	it is valid for the manufacture of	
	- Printing ABERTAINER REINS	WEARING OUR OF THE WEAR OF THE WAR AND THE
1	Sugar	8250
2	Molasses	2625
2	Press mud	3000
		22500
4	Bagasse	15 MW
5	Co-generation	10 177 (

(The cane crushing Capacity of Sugar Industry shall not exceed 2500 TCD)

Conditions under Water (P&CP), 1974 Act for discharge of effluent: 4.

5.5 5.70	in in the second second	Parintial the new ordinal expension of the new ordinal (Clivial)	Sambrids to be adhieved	ो भेषुक्रकार्यः
1.	Trade effluent	275 (Sugar 250 + Co-gen 25)	As per Schedule -l	On land for irrigation
2.	Domestic effluent	41	As per Schedule -I	On land for irrigation

M/s. Vitthal Corporation Pet Ltd. SRO Solapur/I/R/L/59191000

Conditions of decourage and the conditions of emissions

and payages entropy to the conlangsiki: Z. | Boiler No. H (2017/27)

Conditions under Hazardous Waste (V., H & T M) Rules, 2008 for treatment and disposal of hazardous wastel.

Rense in	Company of the Company
Extension and the second secon	. Z221.713
1 Used Spent Oil 5.175.2 10 Kg/D boiler as	

9. Non-Hazardous Solid Wastes:

Sale to Bricks								
1	Fly/Boiler Ash		MT/D	-	Sale to manufacturers/conditioning	for soil		
2	Sludge from waste water treatment	1.25	MT/M		Use as Manure			

- This Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- This consent should not be construed as exemption from obtaining necessary 8. NOC/permission from any other Government agencies.

For and on behalf of the Maharashtra Pollution Control Board

> 1 Land (Dr. P. Anbalagan, IAS) Member Secretary

Received Consent fee of -

Received Consent Ice of –	7.73 7	Lagran Days	disambraya On
Rs. 1,25,000/-	028572	13.06.2014	Bank of India
2 Rs. 1,50,000/-	021369	20.12.2010	Bank of India

Copy to:

- Regional Officer MPCB Pune & Sub -Regional Officer Solapur MPCB, He is directed to ensure the compliance of the consent conditions.
- Chief Accounts Officer, MPCB, Mumbai. 2.
- CC/CAC desk- for record & website updation purposes. 3.

. Considering for compliance of Maco Deligious Consolid

Andreas argues are areas real of the control of the

Ri The Applicant shall operate the efficient treatment manner mann (ETP) to treat the trade efficient so as to achieve the following standards possessed by the Board of under selection. Discount Rules made have dispersioned to time, whichever is subsecti

Sr. No.	Parameters	Standards prescribed by Board
140.		Limiting Concentration in mg/l, except for pH
01	pH	5.5-9.0
02	Oil & Grease	10
03	BOD (3 days 27oC)	100
()4	Sulphate	1000
05	Suspended Solids	100
06	COD	250
07	Chloride	600
08	Total Dissolved Solids	2100

- C] The treated effluent 250 CMD of sugar shall be disposed on own land of 40 acres for gardening/irrigation.
- D) CREP conditions for Sugar Factory
 - i. Operation of ETP shall be started at least one month before starting of cane crushing to achieve desired MLSS. So as to meet prescribed standards from day one the operation of mill.
 - ii. Waste water generation shall be reduced to 100 liters per ton of cane crushed.
 - iii. Industry shall achieve zero discharge into in land surface water bodies.
 - iv. 15 days storage capacity tank shall be provided for treated effluent to take care of no demand for irrigation.
- E] Industry to make necessary arrangement to cover the effluent collection system and to avoid the ingress of Bagasse other material
- F] The unit shall operate ETP even after completion of the crushing season so that any effluent generated during washing & maintenance is discharged after proper treatment.
- G] The unit shall optimize water use in industrial process & maintain records of water consumption & waste water generation.
- 2) A] As per your consent application, you have provided the septic tank & soak pit.
 - Bl The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards.
 - (1) Suspended Solids Not to exceed 100 mg/l. (2) BOD 3 days 27°C Not to exceed 100 mg/l.
 - Cl The treated sewage 41 CMD shall be disposed on land for gardening/irrigation.

M/s Vitthal Corporation Pet Ltd., SRO Solapur/I/R/L/59191000

Page 3 of S

- 2) The inductive entail mass reliaired agreement with the larguest on whose land the treated eithern a contribute of the second separate and a copy of the agreements who value is confined set out the second contribute of the Boston.
- 3) The halfs of shall are to the constant Cell by appointing an Environmental tectories. Chemist and Agraphituse expect for looking after day to day activities of the Environment and impaired where unated effluent is used for infigation.

4) CONDITIONS FOR MOLASSES STORAGE:

- (i) The molasses shall be properly collected and stored in steer tanks which shall be leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- The capacity of tanks for storage of molasses shall be such that it will take care of bumper production of sugar, non-lifting of molasses etc.
- (iii) All the area on which molasses are stored and lembled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board. Intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- (v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near /on the tank.
- (vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines if applicable.

II) Conditions under Water (Prevention & Control of Pollution) CESS Act, 1977 as amended

The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

	Paratone the water constants (19	Water consumption quantity (CMD) (Sugar)
1	Industrial Cooling, boiler feed etc.,	300
2.	Domestic purpose	59
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	125
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are	
	toxic	

M/s. Vitthal Corporation Pvt Ltd., SRO Solapur/I/R/L/59191000

Page 4 of 8

V. Juny

Terms & conditions for curvely was the statistian Control

	ang mga mga mga mga mga mga mga mga mga mg	rected following		•	Tillowing fi	iel patter	
					Firmit	15. 7/A	
1 1	Boiler.No. I	Vi et Serubber		- Бида55C	720 MT/12	0.2%	2880
2	(25 TPH) Boiler No. II (50 TPH)	Wet Serubber	65	Bagasse	580 MT/ID	0.2%	2320

- 2. The Applicant shall provide ESP/ Bag filter/ Wet scrubber to the Bagasse fired botter and Dust Collector to Sugar bagging section as an Air Pollution control equipments OR as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed 150 mg/Nm ³
--------------------	--------------------------------------

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

Sepedule III Details of Bank Guarantees

Sr.	Crossessi	la _{de} ding	Submission	Purpose of BG	Compliance	Validity
No.	(Cros/O/R)	Imposed	Period		Period	Date
3	Renewai of Consent	Rs. 10.0 Lacs	To be extended	consented standards of Effluent. O & M for achieving consented standards of Stack emission.	31.07.2015	30.11.2015

M/s. Vitthal Corporation Pvt. Ltd., SRO Solapur/I/R/L/59191000

Page 6 of 8

the second of the second second

The applicant shall provide facility for maker to the expensal samples and samples of transand the the Board statical the terminal of and Committee and Committee

and a substitution of the I conhient dir quality monthly the applicant shall provide pears in the channel of course of these such as ladder, platform etc. for monitoring the air emissions and the same gone in open for inspection to and for use of the decided state. The claimacytes court attached to the increase of emission shall be designated by numbers such as S. 1. S. 2. etc. and these shall be named displayed to facilitate identification.

Whenever due to any accident or other unioreseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosions inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

The applicant shall promise an alternate electric power source sufficient to operate all poliution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.

The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW (MH&TM) Rules 2008, which can be recycled /processed /reused /recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.

The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M, H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.

An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

10) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

11) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (www.mpcb.gov.in).

12) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.

13) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.

14) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents

15) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

16) Conditions for D.G. Set

Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting

M/s Vitthal Corporation Pvt. Ltd., SRO Solapur/I/R/L/59191000

age options and countries, whichever is on higher Ale 25, material exhaust muffler with The factor of the Arshall also be provided. The enterior of a fill action loss will be done after a factor of the include from a factor of the factors from account to a factor of the factors of the factors

These in bring down norms with a transfer of the principle industrial to the griefly in a superior with a loss advances of DG Set

unanutactore: A project is that see the eventue maintenance procedure for LFO see seems on we and followed in Cusulination with the little manufacturer winder would be by to proceed only with the perfect of DG set from deteriorating with the

D G. Set shall be operated only in case of power tailure

- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. 9)
 - The applicant shall comply with the notification of MoPP dated 17.05,2002 regarding noise limit for generator sets run with diesel.

The industry should not cause any nuisance in corrounding area.

18) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

19) The applicant shall maintain good housekeeping.

20) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.

21) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary

permissions from civic authorities for disposal of solid waste.

22) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.

23) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.

- 24) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 25) The industry shall submit official e-mail address and any change will be duly informed to the
- 26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.
- 27) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or an extension or addition thereto.

28) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of

the operation thereof.

----0000---- (Jakk

M/s. Vitthal Corporation Pet. Ltd., SRO Solopur/1/R/L/59191000