MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701 Fax: 24024068 / 24023516

Website: http://mpcb.gov.in E-mail: ast@mpcb.gov.in



Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

RED/LSI

Consent order No:-Format 1.0/AST/RO-KP/EIC No. KP-16402-14/R/CC- 675 8

Date-[] /06/2015

To,

M/s. Shree Pushkar Petro Products Ltd., Plot No. B-102/103, MIDC Lote Parshuram, Tal. Khed, Dist. Ratnagiri

Subject: Renewal of Consent to Operate RED category.

Ref : 1. Earlier consent to operate is granted vide No. BO/JD PAMS/O-KP/EIC No. KP-9478-12/R/CC-01153 dtd. 06.02.2013

Your application: CR1411000283

Dated: 20.10.2014

For Renewal of Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

1. The consent is granted for a period from 30.11.2014 to 30.11.2017

2. The proposed capital investment of the industry is Rs. 24.13 Crs. (As per C. A Certificate submitted by industry)

3. The Consent is valid for the manufacturing of -

Sr. No.	Product Name	Maximum
		Quantity/UOM
1	Gamma Acid	25 MT/M
2	Metanilic Acid	20 MT/M
3	K-Acid	30 MT/M
4	F. C. Acid	10 MT/M
5	Vinyl Sulphone	40 MT/M
6	H. Acid (to be manufactured by using	25 Mt/M
	spent acid from Vinyl Sulphone plant	
	only	
	ucts mentioned at Sr. No. 1	
```	to 6 shall not exceed 18	50 MT/M
7	Sulphuric Acid	1800 MT/M
8	Oleum 23 %	100 MT/M
9	Oleum 65 %	600 MT/M
10	Chloro-Sulphuric Acid	300 MT/M
	By Products	
1	Di-Calcium Phosphate (to be	9 MT/D
	manufactured by using Acidic Effluent	
	from the products 1 to 4 only in the	
	above list	
2	Power	1 MW
3	Steam	2 MT/Hr.

M/s. Shree Pushkar Petro Products Ltd., SRO Chiplun/I/R/L/39298000

Page 1 of 9

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
Trade effluent	50	As per Schedule -I	СЕТР
Domestic effluent	8	As per Schedule -I	Septic tank
	Trade effluent	quantity of discharge (CMD)  Trade effluent 50	quantity of discharge (CMD)  Trade effluent  50  As per Schedule -I

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr. no.	Description of stack / source	Number of Stack	Standards to be achieved
1.	Boiler-I	1	As per Schedule -II
2.	Boiler-II	1	As per Schedule -II
3.	Sulfuric acid plant	1	As per Schedule -II
4.	Oleum storage tank	1	As per Schedule -II
5.	Chloro Sulphonic acid plant	1	As per Schedule -II

6. Conditions about Non Hazardous Wastes:

Sr. No.	Non-Hazardous waste generation	Quantity Disposal Path	
1	Fly Ash	20 MT/A Landfill/Sale to Brick	KS
L		manufacturer	ĺ

8. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr. No.	Category & Type Of Waste	Sch.I	Quantity	Treatment	Disposal	
1	Process waste (Iron sludge)	26.1	1 MT/D		Sale to MoEF/ SPCB approved reprocessors / Red Oxide manufacturer/ CHWTSDF	
2	Gypsum Sludge	26.1	4 MT/D		Sale to MoEF/ SPCB approved reprocessors / Cement industries/CHW TSDF	
3	Spent Catalyst (V2O3)	17.2	09 MT/M	••••	MoEF/ SPCB approved reprocessors/C HWTSDF	
4	Sulfur sludge	D1	15 MT/M		CHWTSDF	
5	ETP sludge	34.3	06 MT/A		CHWTSDF	

- 9. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 10. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.
- 11. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.

- 12. This consent is issued as per the delegation of powers to HOD's vide Board Office Order No. 31/2013 dtd, 01.03.2013.
- 13. The consent is issued without prejudice of the court order being passed/ passed in Court case no. 31/2003.

For and on behalf of the Maharashtra Pollution Control Board

> (P. K. Mirashe) Assistant Secretary (Tech.)

Received Consent fee of-

Sr. No.	Amount(Rs.)	DD. No.	Date Drawn On
1	1,50,100/-	035504	07.10.2014 SBI Bank

### Copy to:

- Regional Officer -Kolhapur and Sub-Regional Officer, Chiplun, MPCB, -They
  are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk- for record & website updating purposes.

# Schedule-I Terms & conditions for compliance of Water Pollution Control:

1) A] As per your application, you have provided the Effluent Treatment Plant (ETP) of capacity 150 CMD for treatment of 70 CMD Effluent, consists of Primary, secondary and tertiary treatment systems.

B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr No.	Parameters	Standards prescribed by Board
	I. Compulsory Parameters	Limiting Concentration in mg/l, except for pH
01	рН	6.5 to 8.5
02	Suspended Solids	100
03	BOD 3 days 27 deg.0	100
04	COD	250
05	Oil & Grease	10
06	Total Dissolved Solids	2100
07	Sulphate	1000
08	Chloride	600
09	Sulphides	2

C) The overall daily quantity of trade effluent generated from the products mentioned shall not exceed 60 CMD after reuse of 10 CMD of treated effluent for Di calcium Phosphate plant and cooling tower makeup. Out of 60 CMD treated effluent 10 CMD of treated effluent shall be used for manufacturing SSP at Plot No. D-25, MIDC Lote and remaining treated effluent shall be sent to CETP. There shall not be any discharge outside the factory premises.

11)A] As per your consent application, you have provided soak pit as a treatment for sewage.

B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

(1) Suspended Solids.

Not to exceed

100 mg/l.

(2) BOD 3 days 27oC.

Not to exceed

100 mg/l.

C] The treated sewage shall be used on land for gardening/plantation only in the factory premises.

- 12) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition thereto.
- 13) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.
- 14) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

(h)-

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	140
2. 3.	Domestic purpose Processing whereby water gets polluted & pollutants are easily biodegradable	10 150
1.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	NIL
i	For Agriculture/gardening	NIL

15) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.

#### Schedule-II

# Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also proposed to erect following stack (s) and to observe the following fuel pattern-

Sr. No.	Attached To	AVLO	Height	Type of	Quantity & UoM	S %	$SO_2$
1	Boiler-I	Stack with dust collector	31.5	Coal	2.5 MT/M	0.5	Kg/Day
2	Boiler-II	stack	18	<b>j</b>			
3	Sulfuric acid plant	Alkali scrubber	30		****	****	••••
4	Oleum storage tank	scrubber	4	••••	••••		
5	Chloro sulphonic acid plant	scrubber	4				

- 2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	450 /2
		150 mg/Nm3
SO2 Acid Plant	Not to exceed	2.0 Kg/MT of
A -: 1 B#: .		100%acid production
Acid Mist	Not to exceed	30 mg/Nm3

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacemenalteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

me M

### Schedule-III **Details of Bank Guarantees**

Bank Guarantee History: Fresh and Existing BG's

Sr. No.	(C to E/O/R)	Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
1	C to R	5 Lakh	15 days	Towards O & M of Pollution Control Systems.	31.12.2018	30.04.2019

Collins of Day 12.2018 30.04.2t

### Schedule-IV

### **General Conditions:**

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- 3) Industry should monitor effluent quality, stack emissions and ambient air quality monthly.
- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 5) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW (MH&TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall obtain Consent to Operate from Maharashtra Pollution Control Board before actual commencement of the Activity.
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website (<a href="www.mpcb.gov.in">www.mpcb.gov.in</a>).
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

Page 8 of 9

- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set
  - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
  - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
  - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
  - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
  - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
  - f) D.G. Set shall be operated only in case of power failure.
  - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
  - h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 26) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 27) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

----0000-----