# MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701 Fax: 24024068 / 24023516 Website: http://mpcb.gov.in E-mail: jdair@mpcb.gov.in



Kalpataru Point, 2<sup>nd</sup> - 4<sup>th</sup> Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Red/L.S.I

Date: 06/04/2015

Consent No:BO/JD(APC)/EIC No. TN-5434-14/0/CC-4027

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Viraj Profiles Ltd., Plot No.G-22, 23, 32, 33 & 34, MIDC Tarapur, Vill-Boiser, Dist - Palghar.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to: 31/12/2015.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Flat Bars, Round Bars, Angle Bars	20,000	MT/Y
2	Alloy Steel Casting, Steel Casting & Cast Iron Casting (Piece weight below 20 Tons)	48,000	MT/Y
3	Flat & Round (MS & SS Bars) (Without Pickling & surface)	24,000	MT/Y

(Without Pickling & surface treatment activity)

# 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall be NIL
- (ii) The daily quantity of sewage effluent from the factory shall not exceed  $26.0\ M^3$ .
- (iii) Trade Effluent: N.A.
- (iv) Trade Effluent Disposal: N.A.

Page 1 of 5

Viraj Profiles Ltd.- SRO Tarapur I/I/R/L/69644000

- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
- (1) Suspended Solids Not to exceed 100 mg/l. (2) BOD 3 days 27o C. Not to exceed 100 mg/l.
- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

## (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	Furnace & broken slag	80	T/D		Land filling in own
2	Process dust	10	T/D	The second secon	Premises  Land filling in own
viii) Oth	ner Conditions: Indust	ry should me	niton off		Premises

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic	T IOI UIC TOHOW	ing categories is as
(ii) Industrial Processin	11:1-	30.0 CMD
(iii) Industrial C. 1:	ng	0.00 CMD
(iii) Industrial Cooling	- Alla	20.0 CMD
(iv) Agriculture / Garde	ning	45.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

#### **CONDITIONS UNDER AIR ACT:** 5.

- The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
- Control Equipment: -
- Fume extraction system followed by dust collector system of sufficient capacity shall be provided to all sources of SPM/TPM shall be operate & maintain continuously so as to achieve the following standards
- The industry shall take all necessary precautions to control noise pollution in the industrial activities and also nuisance due to vibration generated due to hammering operations. The industry shall take suitable acoustic measures including shielding enclosures noise barriers etc. to control the noise levels within norms stipulated to avoided nuisance in the surrounding
- There shall not any secondary (fugitive) emissions.

#### 6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

### Standards for Emissions of Air Pollutants:

(i) SPM/TPM Not to exceed 150 mg/Nm³
(ii) So2 Not to exceed 286.02 Kg/day

The applicant shall observe the following fuel pattern:

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	3470	Lit/Day
2	LDO	500	Lit/Day

(i) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Roll Mill Drawing Furnace	20
2	AOD 30 Tons (2 Nos)	25
3	Induction Furnace I & II (20 MT)	20
4	Induction Furnace III & IV (20 MT) each	10
5	D.G. Set (1000 KVA)	5.0*
	(* Above roof top of the building in which i	t is installed)

- (ii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (vi) Other Conditions:
- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly

Page 3 of 5

Viraj Profiles Ltd.- SRO Tarapur I/I/R/L/69644000

# 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall not generate any hazardous wastes.

## 8. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

Page 4 of 5

- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 9. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 10. The industry shall submit Bank Guarantee of Rs.5,00,000/- towards operation and maintenance of pollution control system to RO Thane within 15 days period. The Bank Guarantee shall be valid upto 31/04/2016.

11. The Capital investment of the industry is Rs.24.92 /- Crs.

(V.M. Motghare) 674)15

Joint Director (Air Pollution Control)

To, M/s. Viraj Profiles Ltd., Plot No.G-22,23,32,33,34, MIDC Boisar-Tarapur, Tal- Palghar, Dist - Thane.

#### Copy to:

RO- MPCB Thane /SRO-MPCB Tarapur-II

- They are directed to ensure the compliance of consent conditions & submit the status report of pollution control system within 1 month period.

### Received Consent fee of -

DI. 110.	Amount(Rs.)	DD. No.	Date	Drawn On
1 ]	Rs. 1,65,100/-	291533	04/12/2014	Andhra Bank

Balance consent fee of Rs.2,00,000/- will be considered at the time of next consent renewal.