MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 4010437/4020781

/4037124/4035273

Fax

24044532/4024068 /4023516

Email:

enquiry@mpcb.gov.in

Visit At :

http://mpcb.gov.in



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Mumbai - 400 022

Consent order No: -Format 1.0/BO/AS(T)/TN-5921-15/R&A/GEN- 12-257 Date- 30.09.20/5

To.

M/s S D Fine Chem Limited,

Plot No. E-27, E-28, MIDC Tarapur,

Boisar, Tal. & Dist. Palghar - 401 506.

Subject: Renewal of Consent to Operate of existing unit, Consent to 1st Operate for Briquette fired Boiler and Amalgamation of two Consents under RED/MSI category.

Ref.: 1. Earlier Consent granted by the Board vide Consent No. BO/AS(T)/EIC No. TN--13/A/GEN-09314 dtd. 12/11/2013 and No. BO/AS(T)/EIC No. TN-5202-14/E/GEN-8933 dtd. 24/09/2014.

Your application No. CR1506000237

Dated: 20/05/2015

For: Grant of Consent to Operate (150717FT0016)

under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization/ renewal under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- 1. The consent is granted for a period upto 31/05/2020.
- 2. The capital investment of the industry is Rs. 13.40 Crs. as per C.A. Certificate submitted by industry).
- 3. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity
1	Alloxan	
2	Alluminon	35 Kg/M
3	Anthrone	200 Kg/M
4	Benedicts Reagent	62.5 Kg/M
5	Biocide	115 Kg/M
6	Bicine	100 Kg/M
7	1-Butane Sulphonic Acid Sodium Salt	200 Kg/M
8	Creatinine	20 Kg/M
9	Cupferron	54 Kg/M
10	P-Dimethyl Aminobenzaldehyle	30 Kg/M
11	Haemodialysis Fluid	175 Kg/M
12		18,000 Kg/M
	1-Heptane Sulphonic Acid Sodium Salt	20 Kg/M
13	1-Hexane Sulphonic Acid Sodium Salt	20 Kg/M
14	lodophor	200 Kg/M
15	Karl fisher Reagent	60 Kg/M
16	1-Octane Sulphonic Acid Sodium Salt	20 Kg/M
17	Murexide	93 Kg/M
18	Ninhydrin	25 Kg/M
19	Mfg. pH paper	
	<u> </u>	1,500 Pkts/M

		250 T/ ~/N/
20	Piperidinol	350 <u>Kg/M</u>
21	Piperidinol Hydrochloride	325 Kg/M
22	Potassium Phosphate	400 Kg/M
23	Potassium Dichromate	120 Kg/M
24	1-Pentane Sulphonic Acid Sodium Salt	20 Kg/M
25	Phenyl Methane Sulphonyl Chloride	220 Kg/M
26	Succinic Acid Sodium Salt	200 Kg/M
27	Starch	80 Kg/M
28	Triss Hydrochloride	450 Kg/M
29	Aluminium Chloride Hydrated	140 Kg/M
30	Di-Sodium Tetraborate	225 Kg/M
31	Dodeca-Molybdophosphoric Acid	35 Kg/M
32	Dodeca-Tungstophosphoric Acid	30 Kg/M
33	Indole-3-Acetamide	25 Kg/M
34	Repacking of various laboratory/pharmaceutical chemicals, Iron pairing & other reagents, solution and various salts	4,000 MT/A

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. No.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	
1.	Trade effluent		As per Schedule -I	Discharge into CETP
2.	Domestic effluent	2.0	As per Schedule –I	Overflow from soak pit shall be applied on land for gardening

5. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr.	Description of stack	Number of Stack	Standards to be achieved
No.	source		4 C 1 1 1 II
1	Boiler & Thermopack	2	As per Schedule -II
2	Process Vent	4	As per Schedule -II
3	D.G. Set (62.5 KVA)	1	As per Schedule -II

6. Conditions under Hazardous Waste (M,H & TM) Rules, 2008 for treatment and disposal of hazardous waste:

1) The Industry shall handle hazardous wastes as specified below:

Sr.	Type Of Waste			UOM		Disposal
	Distillation Residue	20.3	150	Kg/M	<u></u>	CHWTSDF
2	Off specification products	28.2	10	Kg/M		CHWTSDF
3	ETP Sludge	34.3	700	Kg/M		CHWTSDF

7. Conditions for disposal of Non-Hazardous Waste:

1) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	
1	Ash	100	Kg/D		Sale to Brick Mfrs.
2	Drums, Bags & Packing Materials	60	Kg/M	-	Sale after decontamination

mil)

- 8. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.
- 9. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.
- 10. The applicant shall not carry out expansion of the industry without prior permission of the Board.
- 11. If CETP cannot operate efficiently and problem of pollution occurs, industry should voluntarily stop the production or total effluent should be reused.
- 12. The applicant shall ensure that their production shall be restricted to the generation of effluent as promised by you to the TEPS-CETP by reducing total daily generation of TEPS-CETP with voluntary closure in a staggered manner so as to restrict total generation of TEPS-CETP in a time bound manner to 25 MLD each day. The applicant shall extend the validity of the bank guarantee of Rs. 2.5 lakh for further period upto 31/07/2020 after its expiry.
- 13. The applicant shall not carry out any excess production or produce new products without consent of the Board and without an Environmental Clearance wherever it requires. The applicant shall extend the validity of the bank guarantee of Rs. 2.5 lakh for further period upto 31/07/2020 after its expiry.
- 14. The applicant shall not discharge any effluent in any other source other than the CETP sewerage drain for further treatment and disposal. The applicant shall extend the validity of the bank guarantee of Rs. 1.0 lakh for further period upto 31/07/2020 after its expiry.
- 15. The applicant shall operate and maintain existing ETP effectively and remove all the bypasses, whereby the mode of disposal prescribed in the consent order is not followed. The applicant shall extend the validity of the bank guarantee of Rs. 2.5 lakh for further period upto 31/07/2020 after its expiry.
- 16. The applicant shall make provision for operation & maintenance of flow meter and online pH meter/ separate energy meter to pollution control devices. The applicant shall extend the validity of the bank guarantee of Rs. 1.0 lakh for further period upto 31/07/2020 after its expiry.
- 17. The applicant shall operate and maintain existing Air Pollution Control Systems effectively so as to achieve Consented standards. The applicant shall extend the validity of the bank guarantee of Rs. 2.5 lakh for further period upto 31/07/2020 after its expiry.
- 18. The applicant shall properly collect, transport & regularly dispose off the hazardous wastes to CHWTSDF, in compliance of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules, 2008 and keep proper manifest thereof. The applicant shall extend the validity of the bank guarantee of Rs. 1.5 lakh for further period upto 31/07/2020 after its expiry.
- 19. The applicant shall not carry out any processing while repacking of Laboratory Chemicals and keep proper record thereof. The applicant shall extend the validity of the bank guarantee of Rs. 2.0 lakh for further period upto 31/07/2020 after its expiry.

For and on behalf of the Maharashtra Pollution Control Board

> (P. K. Mirashe) Assistant Secretary (Tech.)

Received Consent fee of-

Sr.	N Amount(Rs.)	DD. No.	Date	Drawn On
1	Rs. 90,000/-	011524	07/11/2013	HDFC Bank
2	Rs. 2,05,000/-	502532	06/05/2015	SBI
3	Rs. 5,000/-	502173	18/06/2015	SBI

(Balance amount of Rs. 45,000/- from previous Consent fees is adjusted)

Copy to:

- Regional Officer (Thane)/ Sub-Regional Officer (Tarapur-I), M.P.C. Board.
 They are directed to ensure the compliance of the consent conditions.
- 2. Chief Accounts Officer, MPCB, Mumbai.
- 3. CC/CAC desk for record & website uploading purpose.

Schedule-I

Terms & conditions for compliance of Water Pollution Control:

- 1) Al As per your application, you have provided ETP of the capacity 20.0 CMD consisting of primary, secondary & tertiary treatment for the treatment of 16.0 CMD industrial effluent.
 - B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent:

Sr. No.	Parameters	Standards prescribed by Board (If any)
	I. Compulsory Parameters	Limiting Concentration in mg/l, except for pH
01	pН	5.5 to 9.0
02	Oil & Grease	10 mg/l,
03	BOD (3 days 27oC)	100 mg/l.
04	TDS	2100 mg/l
	II Additional Parameters	A STATE OF THE STA
05	Suspended Solids	100 mg/l.
06	COD	250 mg/[
07	Sulphates	1000 mg/l
08	Chlorides	600.mg/l.
09	Iron	3 mg/l.
10	Zine	5 mg/l.

- C] The treated effluent shall be recycled/ reused into process upto maximum extent and remaining shall be discharged into CETP for further treatment & disposal. There shall not be any discharge outside the factory's premise.
- 2) A] As per your consent application, you have provided the septic tank followed by soak pit for the treatment of 2.0 CMD sewage. Overflow, if any shall be applied on land for gardening purpose within premise.
 - B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.
 - (1) Suspended Solids. Not to exceed 100 mg/l. (2) BOD 3 days 27oC. Not to exceed 100 mg/l.
- 3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system and/ or extension or addition thereto.
- 4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

min

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water Cess returns in Form-I and other provisions as contained in the said act:

Sr. No.	Purpose for water consumed		er consumption atity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	9	
2.	Domestic purpose	4	-
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	17	
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic		
5.	Others - i) Gardening	50	

6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance/ CREP guidelines.

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC)system and also erected following stack (s) and to observe the following fuel pattern-

	Stack Attached To	APC System	Height in	Type Fuel	Qty. &	S %	
1	Boiler-I (2.0 TPH)	Dust Collector followed by Bag Filter	20	Briquette	3 MT/D	6	Kg/Day 12
2	Boiler-II (0.6 TPH)		18	FO	360 Kg/D	16.2	32.4
3	Thermopack (6 Lac Kcal/Hr)		30	FO	240 Kg/D	10.8	21.6
4	Production Vessel	Scrubber	8	~	e de la companya de l		-
4	Laboratory	Scrubber	8	-		-	-
5	Multi Product Plant	Acidic Scrubber	20	- 1		-	-
6	Multi Product Plant	Alkali Scrubber	20		**************************************	-	-
7	D.G. Set (62.5 KVA)		3 Mtrs (above roof)	HSD	9 Kg/Hr	2.2	4.3

(Oil fired boiler shall be kept standby while other boiler is in operation)

- 2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance/ CREP guidelines.
- 3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	150 mg/Nm ³ .
SO ₂ (FO Boiler)	Not to exceed	32.4 Kg/day
SO ₂ (Briquette Boiler)	Not to exceed	12 Kg/day
		3
Acid Mist/ HCl	Not to exceed	35 mg/Nm ³ .

- 4. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement/alteration well before its life come to an end or erection of new pollution control equipment.
- 5. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

mish

Schedule-III

History of Forfeiture of Bank Guarantees

Sr. No	BG Imposed for C to O/ Directions	Amt. of BG	Amt. of BG Forfeited	Reason of Forfeiture of BG
1	Restart Directions issued vide letter No. MPCB/AS(T)/DIR/B-4983 dtd. 30/10/2013	Rs. 0.5 Lakh	Rs. 1.0 Lakh	Due to non-compliance of condition (g) for irregular disposal of H.W.

Details of Bank Guarantees in force

	r		,		G.	4. 200
Sr.	BG Imposed	Amt. of BG	Submission		Compliance	Validity
No	for	Imposed	Period	Purpose of BG	period	Date
	C to O/]	! 	·		
	Directions			la.		
		ŀ			n. Tari	
1	Restart	Rs. 2.5 lakh	Existing	Condition (a) towards reducing	Continuous	Extend upto
	Directions			total daily effluent generation	Johnnous	31/07/2020
	issued vide			in a staggered manner	e a rem	after expiry
2	letter No.	Rs. 2.5 lakh	Existing	Condition (b) towards not to	Continuous	Extend upto
	MPCB/AS(T)/		_	carry out excess production or		31/07/2020
	DIR/B-4983			produce new products		after expiry
3	dtd. 30/10/2013	Rs. 1.0 lakh	Existing	Condition (c) towards not to	Continuous	Extend upto
	30/10/2013			discharge any effluent in any		31/07/2020
				other source other than the		after expiry
				CETP sewerage drain for		
				further treatment and disposal		
4	;		«			
5		Rs. 1.0 lakh	Existing 🐁	Condition (e) towards	Continuous	Extend upto
			مينينين .	installation and O&M of flow		31/07/2020
			100 AND 1	meter and online pH		after expiry
				meter/separate energy meter to		
		2 2 7 1 1 1	- copy -	pollution control devices		
6		Rs. 2.5 lakh	Existing	Condition (f) towards O&M of	Continuous	Extend upto
		%,,/)	4. 5.2	existing APCS effectively		31/07/2020
7		Rs. 1.5 lakh	Existing	6 1141 (1) 6		after expiry
′		(Existing	Lxisting	Condition (j) for proper H.W.	Continuous	Extend upto
		B.G. Rs. 0.5		Management and to keep proper record of manifest		31/07/2020
		Lakh + Top-		proper record of manifest		after expiry
		up B.G. Rs.				
	s.	1.0 Lakh)				
8	C to O	Rs. 2.0 lakh	Existing	Condition to not to carry out	Continuous	Extend upto
			_	any processing while repacking		31/07/2020
		Ng.		of Laboratory Chemicals and		after expiry
				keeping proper record thereof		



Schedule-IV

General Conditions:

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) If the MIDC pipeline is broken/ overflowing chamber, in such cases industry shall not discharge their treated effluent into MIDC drain, it shall be sent to CETP by tanker.
- 3) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 4) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 5) Whenever due to any accident or other unforcesen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 6) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 7) The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 8) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 9) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 10) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 11) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- 12) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set

min

- a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f) D.G. Set shall be operated only in case of power failure.
- g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel.
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any musance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (formatican downloaded from MPCB official site).
- 26) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 27) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.
- 28) The industry shall recycle/reprocess/reuse/recover hazardous waste as per the provision contained in the HW(M,H & TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which cannot be used for land filling and cannot be recycled/reprocessed etc. should go for that purpose in order to reduce load on incineration and landfill site/environment.

----0000-----

mich