


# MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2 <sup>nd</sup> - 4 <sup>th</sup> Fl.
Fax: 24024068 / 24023516		Opp. Cine Planet Cinema,
Website: <a href="http://mpcb.gov.in">http://mpcb.gov.in</a>		Near Sion Circle, Sion (E)
E-mail: <a href="mailto:mpcb@vsnl.net">mpcb@vsnl.net</a>		Mumbai-400 022.

Red/M.S.I

Consent No: BO/JD(APC)/TB-3/EIC No. PN-24463-15/E-CC-12207 Date: 19/09/2015.

Consent to operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Ganesh Industries .,  
Sr.No.79/2,Shed no.19,At Post Shivane,  
Dangat Industrial Estate, Tal:Haveli, Dist:Pune.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to operate is granted for a period up to: 29.02.2016.
2. The Consent is valid for the manufacture of –

Sr. No.	Product Name	Maximum Quantity	UOM
1	Automobile Components [With Engineering & Zinc & Nickel Electroplating activity ]	50,00,000	Nos/M
2	Aluminum Casting products	75,000	Nos/M

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 3.0 M<sup>3</sup>.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 3.0 M<sup>3</sup>.
- (iii) **Trade Effluent Treatment** : The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	6 to 9.0
2	Temperature	Shall not exceed 5 <sup>o</sup> C above the ambient temperature of the receiving body	
3	Oil & Grease	Not to exceed	10 mg/l
4	Suspended Solids	Not to exceed	100 mg/l.



5	Total metal	Not to exceed	10 mg/l
6	Trichloroethane	Not to exceed	0.1 mg/l
7	Trichloroethylene	Not to exceed	0.1 mg/l
8	Ammonical Nitrogen, as N	Not to exceed	50 mg/l
9	Nickel (as Ni)	Not to exceed	3.0 mg/l
10	Hexavalent Chromium as Cr	Not to exceed	0.1 mg/l.
11	Total Chromium as Cr	Not to exceed	2 mg/l.
12	Sulphides, as S	Not to exceed	2 mg/l.
13	Sulphates as SO <sub>4</sub>	Not to exceed	400 mg/l.
14	Phosphates, as P	Not to exceed	5 mg/l.
15	Copper as Cu	Not to exceed	3 mg/l.
16	Cyanide	Not to exceed	0.2 mg/l.
17	Tin	Not to exceed	2 mg/l.
18	BOD 3 days 27 Deg. C.	Not to exceed	100 mg/l.
19	COD	Not to exceed	250 mg/l.
20	TDS	Not to exceed	2100 mg/l.
21	Total residual chlorine (as Cl <sub>2</sub> )	Not to exceed	1.0 mg/l.
22	Cadmium (as Cd)	Not to exceed	2.0 mg/l
23	Zinc (as Zn)	Not to exceed	5.0 mg/l
24	Lead (as Pb)	Not to exceed	0.1 mg/l.
25	Iron (as Fe)	Not to exceed	4.0 mg/l.

(iv) **Trade Effluent Disposal:** The treated industrial effluent shall be recycled to the maximum extent and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises. There shall not be any discharge into local nalla.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	Suspended Solids	Not to exceed	100 mg/l.
2	BOD 3 days 27o C.	Not to exceed	100 mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be treated in sewage treatment plant. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type	Qty	UOM	Disposal
1	Furnace waste	300	Kg/M	Landfilling
2	Scrap	--	--	Sale

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. **The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

I	Domestic	3.5 CMD
ii	Industrial Processing	3.10 CMD
iii	Industrial Cooling	---- CMD
iv	Agriculture / Gardening	---- CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.



**5. CONDITIONS UNDER AIR ACT :**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**a. Control Equipment: -**

- i. Fume extraction system followed by scrubber provided to furnace and plating section shall be operated properly
- ii. Fume extraction followed by dust collector provided to sources of SPM shall be operated properly.
- iii. There shall not be any secondary (fugitive) emissions.

**b. Standards for Emissions of Air Pollutants:**

i	SPM/TPM	Not to exceed	150 mg/Nm <sup>3</sup>
ii	SO <sub>2</sub>	Not to exceed	10.5 Kg/Day
iii	Acid mist	Not to exceed	35 mg/Nm <sup>3</sup>

**c. The applicant shall observe the following fuel pattern:**

Sr. No.	Type Of Fuel	Quantity	UOM
1	HSD	525	Ltrs/Day

**d. The applicant shall erect the chimney(s) of the following specifications:-**

Sr. No.	Stack Attached	Height in Mtrs
1	DG Set[ 125 KVA]	11.0
2	Melting Furnace	11.0
3	Nickel Electroplating Unit	11.0
4	Zinc Electroplating Unit	11.0


- e. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

**f. Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly

**6. Conditions for D.G. Set**

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.



- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

**7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:**

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Hazardous Waste Category	Qty	UOM	Disposal
1	5.2 Waste /residue containing oil	100	Kg/M	At CHWTSDf
2	Plating metal Sludge	100	Kg/M	At CHWTSDf
3	ETP Sludge	100	Kg/M	At CHWTSDf

- (ii) Treatment: - NIL


1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
  2. The industry should comply with the HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008.
- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
  - b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
  - c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the **Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008** and shown & submitted to the Board as & when asked for.





**8. Industry shall comply with following additional conditions:**

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.



9. The Board reserves the rights to add/amend/revoke any condition in this consent and the same shall be binding on the applicant.
10. Industry shall submit the Bank Guarantee of Rs. 1.0/- Lakhs valid up to 30.06.2016 in the Regional Office Pune within one month period towards operation and maintenance of pollution control system so as to achieve consent standards / and compliance of the same.
11. The Capital investment of the- industry is Rs. 14.61 Crs.

For and On Behalf of the  
Maharashtra Pollution Control Board,

  
(V. M. Motghare) 18/9/15  
Joint Director (Air Pollution Control)

To,  
M/s Ganesh Industries.,  
Sr.No.79/2,Shed no.19,At Post Shivane,  
Dangat Industrial Estate, Tal: Haveli, Dist: Pune.

Copy to:

1. RO- MPCB Pune /SRO-MPCB Pune-II - They are instructed to obtain B.G.of Rs.1.0 Lakhs from industry and submit the Compliance report of the industry along with analysis results within one month period.
2. CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	Rs.2,00,000/-	317558	02.02.2015	Union Bank of India