

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781
/4037124/4035273
Fax : 24044532/4024068 /4023516
Email : enquiry@mpcb.gov.in
Visit At : <http://mpcb.gov.in>



Kalpataru Point, 3rd & 4th floor, Sion- Matunga
Scheme Road No. 8, Opp. Cine Planet Cinema, Near
Sion Circle, Sion (E),
Mumbai - 400 022

Consent order No :- Formate1.0/ BO/CAC-Cell/ EIC No PN-26722/15/14th CAC/ 9967
Date- 01/09/2016

To,
Hindustan Petroleum Corporation Ltd,
Loni Terminal, At-Loni Kalbhor,
Tal-Haveli, Dist Pune.

Subject: Renewal of consent to operate with increase in CI under RED category.
Ref: 1. Existing Consent granted vide no. Formate1.0/BO/CAC-Cell/EIC NoPN-
23008-14/23rd CAC/1775 dtd 13.02.2015.
2. Your application approved in CAC meeting held on 02.02.2016.

Your application: CR1509000152
Dated: 01.07.2015

For: Renewal of consent to operate with increase in CI under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

1. The consent is granted for a period from 01.08.2015 upto 30.06.2020.
2. The actual capital investment of the industry is Rs.153.65 Crs. (As per C.A. Certificate submitted by industry)
3. The Consent is valid for the storage and handling of Petroleum Products to the maximum capacity of 213198 KL at a time.

Sr. No.	Tank No	Product Name	Maximum Quantity at a time in KL
1	704	Motor Spirit	9699
2	706	Motor Spirit	4558
3	703	Motor Spirit	9641
4	705	Motor Spirit	4455
5	720	Motor Spirit	23869
6	105	Motor Spirit	7350
8	101	High Speed Diesel	10105
9	102	High Speed Diesel	10118
10	103	High Speed Diesel	11000
11	104	High Speed Diesel	7344
12	701	High Speed Diesel	22997
13	702	High Speed Diesel	23587
14	718	High Speed Diesel	23344
15	719	High Speed Diesel	10531
16	106	Superior Kerosene Oil	9900
17	107	Superior Kerosene Oil	7350
18	108	Superior Kerosene Oil	5650
19	109	Superior Kerosene Oil	5650
20	721	Ethanol	535

21	714	Ethanol	396
22	722	Ethanol	45
23	711	Slop	399
24	712	Slop	399
25	717	Ethanol	4276
Total			213198

4. Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. no.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
1.	Trade effluent	40	As per Schedule -I	On land for gardening
2.	Domestic effluent	30	As per Schedule -I	

5. Conditions under Air (P&CP) Act, 1981 for air emissions:

Sr. no.	Description of stack / source	Number of Stack	Standards to be achieved
1.	DG sets (500 KVA & 250 KVA)	2	As per Schedule -II


6. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr. No.	Type Of Waste	Category	Quantity	UOM	Treatment	Disposal
1	Waste/residues containing oil	5.2	2	MT/M		CHWTSDF

7. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.

8. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.

For and on behalf of the
Maharashtra Pollution Control Board


(Dr. P. Anbalagan, IAS)
Member Secretary

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	922013	145863	26.06.2015	SBI
	50000	147395	13.10.2015	SBI
2	638879	1309901	11.07.2016	SBI

Copy to:

1. Regional Officer -Pune and Sub-Regional Officer-Pune-2, MPCB, They are directed to ensure the compliance of the consent conditions.
2. Chief Accounts Officer, MPCB, Mumbai.
3. CC/CAC desk- for record & website updation purposes.

Schedule-I

Terms & conditions for compliance of Water Pollution Control:

1) A] As per your application, you have provided the Effluent Treatment Plant (ETP) with the design capacity of 150 CMD.

B] The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Sr No.	Parameters	Standards prescribed by Board (If any)
		Limiting Concentration in mg/l, except for pH
01	pH	5.5 -9.0
02	Oil & Grease	10
03	BOD (3 days 27°C)	100
04	Total Dissolved Solids	2100
05	Suspended Solids	100
06	COD	250
07	Chloride	600
08	Sulphate	1000

C] The treated effluent shall be disposed on land for gardening.

2) A.] As per your consent application, you have provided septic tanks and soak pits

B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

- | | | | | |
|-----|-------------------|---------------|-----|-------|
| (1) | Suspended Solids. | Not to exceed | 50 | mg/l. |
| (2) | BOD 3 days 27°C. | Not to exceed | 30 | mg/l. |
| (3) | COD | Not to exceed | 100 | mg/l. |

C] The treated sewage shall be disposed on land for gardening.

3) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or /and extension or addition thereto.


4) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

5) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water

...
- meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	0
2.	Domestic purpose	40
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	50
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	0
5.	Agriculture	5

- 6) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act,1986 and rule made there under from time to time/ Environmental Clearance / CREP guidelines.
- 7) Necessary arrangements for collection & treatment of leachate/tank bottom generated underneath the storage tank should be made along with provisions of Oil skimmers & necessary treatments arrangements for same.
- 8) Monitoring of ground water (through Piezometric wells) and soil at appropriate places at regular intervals (every 3 months) should be carried out to ascertain that these are not getting polluted while operating the booster station.


Maharashtra Pollution Control Board

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

1. As per your application, you have provided the Air pollution control (APC) system and also erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached To	APC System	Height in Mtrs.	Type of Fuel	Quantity & UoM	S %	SO ₂ Kg/Day
1	DG sets (500 KVA & 250 KVA)	stack	5.5 mtrs each above the roof of the building	HSD	60 LTRS/D	1	1.2

2. The Applicant shall provide Specific Air Pollution control equipments as per the conditions of EP Act, 1986 and rule made there under from time to time / Environmental Clearance / CREP guidelines.
3. The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	150 mg/Nm ³ .
--------------------	---------------	--------------------------

4. Standards for Emissions of VOC Pollutants:

Sr.No	Compounds	Maximum emission limit (mg/Nm ³), dry basis
1	MA,PA,Phenol	20
2	Ethyl benzene (EB), Styrene, Toulene, Xylene, Aromatics, EG, PG	100
3	Non-methane HC (Paraffin), Acetone, olefins	150

5. Storage of Volatile Liquids : General Petroleum Products

(1) Storage tanks with capacity between 4 to 75m³ and total vapour Pressure (TVP) of more than 10 kpa should have Fixed Roof Tank (FRT) with pressure valve vent.

(2) Storage tank with the capacity between 75 to 500 m³ and total vapour Pressure (TVP) of 10 to 76 kpa should have Internal Floating Root Tank (IFRT) of External Floating Root Tank (EFRT) or Fixed Roof Tank with vapour control or vapour balancing system.

(3) Storage tanks with the capacity of more than 500 m³ and total vapour Pressure (TVP) of 10 to 76 kpa should have Internal Floating Roof Tank or External Floating Roof Tank or Fixed Roof Tank with vapour control system.

(4) The tanks with the capacity of more than 75 m³ and total vapour Pressure (TVP) of more than 76 kpa should have Fixed Roof Tank with vapour control system.

(5) Requirement for seals in Floating Roof Tanks:

(i) (a) IFRT and EFRT shall be provided with double seals with minimum vapour recovery of 96%.

(b) Primary seal shall be liquid or shoe mounted for EFRT and vapour mounted for IFRT. Maximum seal gap width will be 4 cm and maximum gap area will be 200 cm²/m of tank diameter. (c) Secondary seal shall be rim mounted. Maximum seal gap width will be 1.3 cm and maximum gap area will be 20 cm²/m of tank diameter. (d) Material of seal and construction shall ensure high performance and durability.

(ii) Fixed Roof Tanks shall have vapour control efficiency of 95% and vapour balancing efficiency of 90%

(iii) Inspection and maintenance of storage tanks shall be carried out under strict control. For the inspection, API RP 575 may be adopted, In-service inspection with regard seal gap should be carried out once in every six months and repair to be implemented in short time. In future, possibility of on-stream repair of both seals shall be examined.

6. Solvents for Lube-Base Oil production (Furfural, NMP, MEK, Toluene and MIBK)

IFRT with double seals and inert gas blanketing with vapour removal efficiency of at least 97% shall be provided.

Emission control for Road tank truck/Rail tank wagon loading		
Loading of Volatile Products	Gasoline and Naphtha:	
	(i) VOC reduction, %	(i) 99.5
	(ii) Emission, gm/m ³	(ii) 5
	Benzene:	
	(i) VOC reduction, %	(i) 99.99
	(ii) Emission, mg/m ³	(ii) 20
	Toluene/Xylene:	
	(i) VOC reduction, %	(i) 99.98
	(ii) Emission, mg/m ³	(ii) 150
Note:		
(i) It shall be applicable for Gasoline, Naphtha, Benzene, Toluene and Xylene loading.		
(ii) Road tank Truck shall have Bottom loading and Roll tank wagon shall have Top submerged loading.		

(iii) Annual leak testing for vapour collection shall be done


7. The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement well before its life come to an end or erection of new pollution control equipment.
8. The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).
9. High level alarm synchronized with cut off capacity should be provided to the storage tank
10. The products/chemicals should be properly stored in tanks which should be absolutely leak proof. At no stage of handling, there should be leakage or spillage.
11. The project authority should prepare On-site & Off-site emergency preparedness plan based on detailed risk analysis.
12. The internal roads should be cement concrete and should maintain adequate green belt.



Schedule-III
Details of Bank Guarantees

Sr. No.	Consent (C to E/O/R)	Amt of BG Imposed	Submissi on Period	Purpose of BG	Complian ce Period	Validity Date
1	C to O	Rs 5 lakhs*	Submitted	O & M of pollution control systems	30.06.2020	30.10.2020

*The BG of Rs 5 lakh obtained towards O & M of PCS shall be extended for a period upto 30.10.2020.



Maharashtra Pollution Control Board

Schedule-IV

General Conditions:

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) Industry should monitor effluent quality, stack emissions and ambient air quality monthly.
- 3) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 4) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 5) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 6) The firm shall submit to this office, the 30th day of September every year , the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 7) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 8) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 9) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 10) **The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.**
- 11) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act, 1981 and Environmental Protection Act, 1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 12) The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Wastes (M,H &TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 13) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 14) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.

- 15) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 16) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 17) Conditions for D.G. Set
- Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
 - Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
 - D.G. Set shall be operated only in case of power failure.
 - The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
 - The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel
- 18) The industry should not cause any nuisance in surrounding area.
- 19) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 20) The applicant shall maintain good housekeeping.
- 21) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 22) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 23) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 24) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 25) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dtd. 16.11.2009 as amended.

—0000—

