

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781
/4037124/4035273
Fax : 24044532/4024068 /4023516
Email : enquiry@mpcb.gov.in
Visit At : <http://mpcb.gov.in>



Kalpataru Point, 3rd & 4th floor, Sion- Matunga
Scheme Road No. 8, Opp. Cine Planet Cinema, Near
Sion Circle, Sion (E),
Mumbai - 400 022

Red/L.S.I

Date: 19/Nov/2011

Consent No: BO/PAMS/R/EIC NO.NM-2177-10/CC-14

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Indian Oil Corporation Ltd
Plot No. T-20, MIDC Talaja,
Dist-Raigad

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.03.2013
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	SERVO BRAKE FLUID SUPER HD - 210L BRL	50	KL/M
2	SERVOSYSTEM FG 68 - 210 L BRL	4	KL/M
3	SERVOCONVAL 46 - 210L BRL	1.8	KL/M
4	SERVOLINE 100 - 210L BRL	2.2	KL/M
5	SERVOLINE 150 - 210L BRL	2.2	KL/M
6	SERVOFILM 100 - 210L BRL	12.58	KL/M
7	SERVOFILM 460 - 210L BRL	10.8	KL/M
8	SERVOSPIN 2 - 210L BRL	3.6	KL/M
9	SERVOSPIN 12 - 210L BRL	14	KL/M
10	SERVOSPIN 22 - 210L BRL	20	KL/M
11	SERVOSPIN EE 10 - 210L BRL	2.6	KL/M
12	SERVOSPIN 5 - 210L BRL	10.5	KL/M
13	SERVO KNIT CLEAN 32 - 210L BRL	4.1	KL/M
14	SERVO SYNGEAR 220 - 210L BRL	10	KL/M

15	SERVO SYNGEAR 320 - 210L BRL	1.6	KL/M
16	SERVOSYNGEAR 460-210L BRL	2	KL/M
17	SERVOFRIZ NH 68 - 210 L BRL	3.2	KL/M
18	SERVOFRIZ ECO 68 - 210L BRL	2	KL/M
19	SERVOFRIZ ECO 150 - 210 L BRL	2	KL/M
20	SERVOQUENCH 11-210L BRL	18	KL/M
21	SERVOQUENCH 707-210L BRL	4.4	KL/M
22	SERVOQUENCH C 11-210L BRL	7.9	KL/M
23	SERVOCUT 945 - 210L BRL	68	KL/M
24	SERVOCUT BR - 210L BRL	1.68	KL/M
25	SERVOCUT GR - 210 L BRL	30	KL/M
26	SERVOCUT 151 - 210L BRL	9.51	KL/M
27	SERVOCUT 201 - 210L BRL	4.62	KL/M
28	SERVOCUT 253 - 210L BRL	5.96	KL/M
29	SERVOCUT 353 - 210L BRL	2	KL/M
30	SERVOHONE 7-210L BRL	60	KL/M
31	SERVOGRIND 12-210L BRL	2	KL/M
32	SERVOMET 033-210L BRL	12.6	KL/M
33	SERVO RP 125-210L BRL	16.53	KL/M
34	SERVO RP 200 - 210L BRL	8.75	KL/M
35	SERVO RP 103 WD - 210L BRL	9.89	KL/M
36	SERVO RP 104 WD-210L BRL	80	KL/M
37	SERVOTELESHOCAB-210L BRL	2	KL/M
38	SERVO SHOCAB ES-210L BRL	1.2	KL/M
39	SERVOCRESS 68 -210 L BRL	1.8	KL/M
40	SERVOCRESS 150 - 210 L BRL	1.2	KL/M
41	SERVOSYNCO E 46-210L BRL	1.2	KL/M
42	SERVOSYNCO E 68-210L BRL	1.2	KL/M
43	SERVOSYNCO E 100 - 210L BRL	0.63	KL/M
44	SERVOSYNCO E 150 - 210L BRL	1.2	KL/M
45	SERVOSYNGEAR 460 RR - 210L BRL	9.07	KL/M
46	SERVO THERM MEDIUM - 210L BRL	16.72	KL/M
47	SERVO THERM SPECIAL - 210L BRL	6.6	KL/M
48	SERVOTHERM S MEDIUM -210L BRL	6.3	KL/M
49	SERVOTORQUE 10-210L BRL	28.78	KL/M
50	SERVO TRANSTRAC HVI - 210 L BRL	1.2	KL/M
51	SERVO STEEROL 22(j) L - 210L BRL	40	KL/M
52	SERVOSTEEL EP 100 PLUS - 210 L BRL	2	KL/M
53	SERVO DS 2 - 168 KG DRM	1.8	KL/M
54	SERVOELECTRA - 210L BRL	26	KL/M
55	SERVO DMFA - 210 L BRL	1	KL/M
56	HYUNDAI SERVO COOLANT - 210L BRL	20	KL/M
57	SERVO KOOL PLUS -210L BRL	60.76	KL/M
58	SERVOFYRESS HFDU 46 ES - 210 L BRL	2	KL/M

59	SERVO KOOL READY-210L BRL	1.5	KL/M
60	SERVO KOOL NFSC - 210 L BRL	1.3	KL/M
61	SERVO KOOL TM - 210 L BRL	100	KL/M
62	SERVO RP 102 WD - 210L BRL	2.8	KL/M
63	SERVO CUBROL 210 LTR BRL	2	KL/M
64	UNIVYS N-46 - 210 L BRL	2	KL/M
65	SERVO CUT 375	2	KL/M
66	SYNLOCK 10 BULK	1	KL/M
67	SYNLOCK 10 BULK	1	KL/M
68	SYNGEAR AMP 320	15	KL/M
69	LUBREX 22	10	KL/M
70	WAY 32	2	KL/M
71	WAY 68	2	KL/M
72	WAY 220	2	KL/M
73	WAY 100	2	KL/M
74	WAY H 32	2	KL/M
75	WAY H 57	2	KL/M
76	WAY H 68	2	KL/M
77	MESH PLUS 100	2	KL/M
78	MESH PLUS 150	2	KL/M
79	MESH PLUS 220	20.2	KL/M
80	MESH PLUS 320	10	KL/M
81	MESH PLUS 460	26	KL/M
82	SPARK 2	2	KL/M
83	LUBREX 150	12	KL/M
84	RP 180 ES (WR requirements only)	12	KL/M
85	CALIB 2	2	KL/M
86	CALIB 5	2	KL/M
87	SERVOSYNTH 5	8.5	KL/M
88	SERVO QUENCH 107	12	KL/M
89	SERVOCUT 335	6.09	KL/M
90	SERVOSPARK 2	5.37	KL/M
91	SERVO FYRESS WG 46	1.35	KL/M
92	SERVO KOOL ST	2.1	KL/M
93	SERVO ANTI CORR BF	10	KL/M
94	SERVO WAY 100	4	KL/M
95	SERVO SYNGEAR 320 PLUS	6.99	KL/M
96	SERVO RP 180 ES	7.3	KL/M
97	SERVOCUT GR - BULK	216	KL/M
98	SERVO KOOL TM - BULK	120	KL/M
99	SERVOFILM 12 - BULK	54	KL/M
100	IOC PROCESS OIL - BULK	18	KL/M
101	SERVO BRAKE FLUID SUPER HD -20X1/2L- HDPE	8	KL/M
102	KOOL READY (10X1)	1.46	KL/M

103	SERVO TRANSTRAC HVI - 20 X 1/2 L HDPE	8	KL/M
104	HYUNDAI COOLANT (10X1)	12	KL/M
105	KOOL PLUS (10 X 1)	16.5	KL/M
106	SERVO KOOL PLUS-20X1/2L-HDPE	5.4	KL/M

The industry should maintain the total production quantity 1378 KL /Month

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 25.0M³.

(ii) The daily quantity of sewage effluent from the factory shall not exceed 10.0M³.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
2	BOD 3 days 27 deg C	Not to exceed	100 mg/l
3	Oil & Grease	Not to exceed	10 mg/l
4	Suspended Solids	Not to exceed	100 mg/l.
5	COD	Not to exceed	250 mg/l.
6	Sulphates	Not to exceed	1000 mg/l.
7	TDS	Not to exceed	2100 mg/l.
8	Zinc	Not to exceed	5.0 mg/l.

(iv) Trade Effluent Disposal: The treated effluent shall be recycled to the maximum extent and remaining treated effluent shall be sent to CETP. There shall not be any discharge outside the factory premises.

(v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1		Not applicable		

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose	12.00 CMD
(ii) Water gets Polluted & Pollutants are Biodegradable	0.00 CMD
(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic	0.00 CMD
(iv) Industrial Cooling, spraying in mine pits or boiler feed	29.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. **Control Equipment:**

- I. Air pollution control system of sufficient capacity shall be provided to all dust generating locations and operated properly.
- II. There shall not be any secondary (fugitive) emissions.

b. **Standards for Emissions of Air Pollutants:**

(i) SPM/TPM	Not to exceed	150 mg/Nm ³
(ii) SO ₂	Not to exceed	315.0 Kg/day

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

7. Standards for Stack Emissions:

- (i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	3.50	MT/Day

- (ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler	38.00
2	D.G. Set (380 KVA)	8.00

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (v) Other Conditions:
 - 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality Regularly.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
-NA-				

- (ii) Treatment: - NIL

- 9. Whenever due to any accident or gas leakage or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of Industry, Safety and Health, Police Station, Fire Brigade, Directorate of Health Services, Department

of Explosives, Board and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emission and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.

10. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste - The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

8. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
11. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
12. If CETP does not operate efficiently and problem of pollution occurs, industry should voluntarily stop the production or total effluent should reuse.
13. This consent is issued as per the decision taken in the meeting of the Consent Committee of the Board held on 04/11/2011 with the approval of Hon'ble Chairman of the Board.
14. The Capital investment of the industry is ₹ 37.43 Crore


 15.11
 (Milind Mhaiskar)
 Member Secretary

To,
 M/s Indian Oil Corporation Ltd
 Plot No. T-20, MIDC Talaja,
 Dist-Raigad

Copy to:-

Rel. Office Mumbai (SRO, Talaja Navi Mumbai III)

-- They are directed to ensure the compliance of consent conditions.
 CAO/Cess Branch/Master file.

Received Consent fee of -

Sr. No.	Amount (Rs.)	DD. No.	Date	Drawn On
1	150000/-	500369	06 Nov 2011	SBI Bank