

MAHARASHTRA POLLUTION CONTROL BOARD

24010437/24026781/24014701

Kalpataru Point

24024089/74023516

Opp. Cine Planet Cinema

Plot No. 107, Sector 10, Navi Mumbai

Near Sion Circle, Sion (E)

24024089/74023516

Mumbai - 400 022

R/PD/L.S.I.

Consent No: BO/JD (APC)/EIC NO.NK - 9987-11/R/CC- 18 Date 19 / 11 / 2011

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008.

[To be referred as Water Act, Air Act and HW (M, H & TM) Rules respectively].

CONSENT is hereby granted to

M/s. Graphite India Ltd.
Cut No. 523/524, A/P Gonde Village,
Tal. Igatpuri, Dist. Nashik.

located in the area declared under the provisions of the Water Act, Air Act and Authorization under the provisions of HW(M,H & TM) Rules thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to- 31/08/2014.

2. The Consent is valid for the manufacture of -

Sl. No.	Product Name	Maximum Capacity	
		Quantity	Unit
1	GRP Pipes, Coupling & Tanks	10640	MT/Annum
2	Resin	3065	MT/Annum

TERMS & CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed: 13.50 M³
- (ii) The daily quantity of sewage effluent from the factory shall not exceed: 13.10 M³
- (iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Sl. No.	Parameter	Units	
I	pH	Between	5.5 to 9.0
	Suspended Solids	Not to exceed	100 mg/l
III	BOD 3 days 27 Deg. C	Not to exceed	100 mg/l

1	COD	Not to exceed	250	mg/l
5	Oil & Grease	Not to exceed	10	mg/l
6	TDS	Not to exceed	2100	mg/l
7	Chlorides	Not to exceed	600	mg/l
8	Sulphates	Not to exceed	1000	mg/l

(iii) Trade Effluent Disposal: The treated effluent shall be reused in the process to the maximum extent and remaining shall be disposed on land for gardening/plantation in the premises only. There shall not be any discharge outside the factory premises. The industry shall become member of CETP as and when required.

Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l
(2)	BOD 3 days 27° C.	Not to exceed	100	mg/l

(iv) Sewage Effluent Disposal: The treated domestic effluent shall be used on land for gardening / plantation only. There shall not be any discharge outside the factory premises.

(v) Non - Hazardous Solid Wastes:

No.	Description	Quantity	From	To/where	Disposal
1	Fab Cutting & composite glass fiber residues	51.50	MT/Annum	...	By Sale
2	Dust/Sand from dust collector	10.00	MT/Annum	...	By Sale

(vi) Other Conditions: Industry should monitor effluent quality regularly.

(vii) The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and rules there under:

The daily water consumption for the following categories is as under:

(i) Domestic	...	16.40	CMD
(ii) Industrial Processing	...	20.60	CMD
(iii) Industrial cooling	...	10.20	CMD
(iv) Agriculture/Gardening	...	20.00	CMD

(viii) The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

6. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

7. Control Equipments:

Dust Collector of sufficient capacity provided to E-2 machines,

Shell cutting section shall be operated & maintain properly so as to achieve following emission standards.

- (2) There shall not be any secondary (fugitive) emissions

5. CONDITIONS FOR DG Set:

- (1) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- (2) The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75dB (A) during day time and 70 dB (A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- (3) The applicant should make efforts to bring down noise level due to DG set outside industrial premises, within ambient noise requirements by proper screening and control measures.
- (4) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- (5) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- (6) D.G. Set shall be operated only in case of power failure.
- (7) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

Standards for Emissions of Air Pollutants:

(i)	SPM/TPM	Not to exceed	150.0 mg/Nm ³
(ii)	SO2	Not to exceed	11.22 Kg/Day

- (i) The applicant shall observe the following fuel pattern:-

		OPEN CYCLE	CLOSED CYCLE
1	LPG	400	Lit./Day
2	Diesel	60	Lit./Day

- (ii) The applicant shall erect the chimney (s) of the following specifications:-

	CHIMNEY SPECIFICATIONS	PIPELINE LENGTH
1	DG Set (625 KVA)	3.5 (above the roof)
2.	Thermic Fluid Heater	30

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

- (iv) The industry shall take adequate measures for control of noise levels from

from own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

Other Conditions:

- (i) The industry should not cause any nuisance in surrounding areas.
- (ii) The industry should monitor stack emissions and ambient air quality regularly.

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below:

Sl. No.	Hazardous Waste	Quantity	Unit	Category
1	23.1 Resin Distillate	20.0	MT/Annum	CHWTSDF
2	33.3 Empty containers/barrels/Cans	2180	Nos./Annum	CHWTSDF/MP: B authorized recycler
3	34.3 Chemical sludge from waste water treatment and the Sludge from tile mess	31.0	MT/Annum	CHWTSDF

- (i) Treatment - NIL

- (i) The authorization is hereby granted to operate a facility for storage, transport & disposal of hazardous waste.
- (ii) The industry should comply with the Hazardous Waste (Management, Handling & Transboundary Movement) Rules, 2008.
- (iii) Whenever due to any accident or other unforeseen act or event, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- (iv) The unit has to display and maintain the data online outside the factory premise in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- (v) It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management, Handling & Transboundary Movement) Rules, 2008 and shown & submitted to the Board as & when asked for.

8. Industry must comply with following additional conditions:

- (i) The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- (ii) The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- (iii) Solid waste - The non hazardous solid waste arising in the factory premise, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- (iv) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to mitigate

compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board's staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

The Firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environmental Protection (Second Amendment) Rules, 1992.

An inspection book shall be opened and made available to the Board's office during their visit to the applicant.

The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and a pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the rivers / canals down-stream of the terminal manholes. No effluent shall find its way out of plant in designed and provided collection System.

Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

This consent is issued pursuant to the decision of the Consent Committee meeting of the Board held on 4.11.2011.

The Board reserves the rights to add/amend/revoke any condition in this consent and the same shall be binding on the applicant.

The Capital Investment of the industry is Rs. 40.77 Crores.

Milind Mhaskar, IAS
Member Secretary

W.W. G. Spill India Ltd.
Gin No. 523/524, A/P Gondi Village,
Tal. Igatpuri, Dist. Nashik

Received Consent fee of -

Sl. No.	Date	Amount (Rs.)	Bank
1	24/08/2011	103248	HFPC Bank Ltd.
2	19/10/2011	103359	HFPC Bank Ltd.

Consent Fees received as per revised consent fee GR of Env Deptt, G.O.M, dated 25.1.2011

Copy to:

1. CAQ/Cess Branch/Master File.
2. NO- MPCB, Nashik/SRO- MPCB, Nashik 3. Master file.