## MAHARASHATRA POLLUTION CONTROL BOARD Kalpataru Point, 3rd & 4th floor, Sion- Matunga

Phone

Visit At :

Fax

4010437/4020781 /4037124/4035273

http://mpcb.gov.in

24044532/4024068 /4023516



Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Mumbai - 400 022

Email enquiry@mpcb.gov.in

Red/L.S.I

Date: 23 /Dec/2011

Consent No: BO/PAMS/R/EIC NO.RD-2185-11/CC-CAC-95

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act. 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to M/s Konkan Synthetic Fibers (Poly). Unit Ltd. C-61 (Part-B), Mahad , Mahad Raigad, Maharashtra

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

# 1. The Consent to Operate is granted for a period up to:. 30.06.2012

#### 2. The Consent is valid for the manufacture of -5 8

Sr. No.	Product Name	Maximum Quantity	UOM
1	Partially Oriented Yarn (POY), Highly Oriented Yarn	910	MT/M

# 3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed  $28.00 M^3$ .

(ii) The daily quantity of sewage effluent from the factory shall not exceed  $10.00 M^3$ . (iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:


1	pH	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	100	mg/l.
4	COD	Not to exceed	250	mg/l.
5	Oil & Grease	Not to exceed	10	mg/l.
6	TDS	Not to exceed	2100	mg/l

- (iv) Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall be discharged in to drainage system provided by MIDC.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow if any, shall be used on land for gardening / plantation only.

#### (vii) Non-Hazardous Solid Wastes: -



(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose	15.00 CMD
(ii) Water gets Polluted &	
Pollutants are Biodegradable	18.00 CMD
(iii) Water gets Polluted, Pollutants	
are not Biodegradable & Toxic	0.00 CMD
(iv) Industrial Cooling, spraying	
in mine pits or boiler feed	253.00CMD
(v) Agriculture / Gardening	25.00 CMD
The applicant chall regularly submit to	the Board the

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

## 5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

### **Control Equipment:**

- a) Fume Extraction system followed by dust collector, scrubber of sufficient capacity shall be provided to all dust generating locations and shall be operated properly and continuously.
- b) There shall not be any secondary (fugitive) emissions

## **Standards for Stack Emissions:**

1)	SPM	Not to exceed	150	mg/Nm3
2)	SO2	Not to exceed	500	kg/day

(ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil /LDO	8	MT /M

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.	
1	Boiler	30.00	
2	Boiler	30.00	
3	D.G. Set (2270 KVA)	35.00	
4	D.G. Set (2270 KVA)	35.00	

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

#### (vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

## 6. Conditions for D.G. Set :

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

# 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

## (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	5.1 Used /spent oil			Sale to authorized actual
2	5.2 Wastes/residue containing oil	800.00	Lit/M	user/ reprocessor
3	34.3 Chemical sludge from waste water treatment	25.0	Kg/M	CHWTSDF

- (ii) Treatment: NIL
- 8. Whenever due to any accident or gas leakage or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of Industry, Safety and Health, Police Station, Fire Brigade, Directorate of Health Services, Department of Explosives, Board and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emission and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.
- 9. Industry shall comply with following additional conditions:
  - i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
  - ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
  - iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
  - iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
  - v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii.The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 10. If CETP does not operate efficiently for achieving standards and problem of pollution occurs, industry shall voluntarily stop the production or total effluent shall be reused.
- 11. The consent should not be construed as any exemption form obtaining necessary NOC from other Govt. agencies as may deemed fit necessary.
- 12. The industry shall submit the Bank Guarantee of Rs.5.00 lacs for timely submission of information.
- 13. This consent is issued as per the decision taken in the meeting of the Consent Appraisal Committee of the Board held on 07/12/2011.
- 14. The Capital investment of the industry is Rs. 132. 61. Crore

(Milind Mhaiskar, IAS) Member Secretary

## M/s Konkan Synthetic Fibers (Poly) Unit Ltd. C-61 (Part-B), Mahad ,Mahad Raigad,Maharashtra

Copy to :

To,

RO, Raigad /SRO Mahad.

-- They are directed to collect the B.G. of Rs 5.0 lacs and ensure the compliance of consent conditions.

CAO/Cess Branch/Master file.

## Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	397860/-	245908	21 May 2011	Bank of Maharashtra