MAHARASHATRA POLLUTION CONTROL BOARD

Phone:

24010437/24020781

Fax

24024068 / 24023516

Email Visit At: mpcb@vsnl.net

http://mpcb.gov.in



Kalpataru Point, 2nd - 4th Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

PN-

Infrastructure/Orange/L.S.I Consent No. BO/RO(HQ)/CO/CAC- 89

Date 22/Dec/2011

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

CONSENT is hereby granted to

M/s Eon Kharadi Infrastructure Pvt. Ltd. Plot No. 1, S.No. 77, Kharadi Knowledge Park, Kharadi, Pune- 411014

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to 31/01/2013

......

2. The Consent is valid -

For IT project named as M/s Eon Kharadi Infrastructure Pvt. Ltd. at Plot No. S.No. 77, Kharadi Knowledge Park, Kharadi, Pune- 411014, on total plot area of 1,80,000.00 Sq mtrs and total Built up area of 2,51,745.12 Sq mtrs including services and utilities as per occupation certificate issued by local body.

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall be Nil.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 1293.00M³.
- (iii) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	рН	Not to exceed	6.5 to 9.0
3	Suspended Solids	Not to exceed	100 mg/l.
4	BOD 3 Days 27 degree C	Not to exceed	100 mg/l,
5	Fecal Coliform	Not to exceed	500/100/1 mg/l.
6	Residual Chlorine	Not to exceed	01 mg/l.
7	Detergent	Not to exceed	01 mg/l.
8	Floating matters	Not to exceed	10 mg/l

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting and cooling of Air conditioners etc. In no case, effluent shall find its way to any water body directly/indirectly at any time.

Project proponent shall operate STP for five years from the date of obtaining Occupation Certificate.

(vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	Biodegradable Waste	1.60	Ton/D	Composting	Composting
2	Non-Biodegradable Waste	2.40	Ton/D	-	Through Local Body
3	e-Waste	1.50	Ton/D		Sale to Authorized Reprocessor.

(viii)Other Conditions

- 1. All activities shall be in resonance with the provisions of Indian Forest Act, 1927 (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.
- 2. There shall be no felling of trees whether on Forest, Government, Revenue or Private lands except as per prevailing Rules.
- 3. Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable.
- 4. Near the activities that are related to water (like activity of water parks, water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.
- 5. In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.
- 6. The Applicant shall segregatesolid wastes into biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting (i.e vermi-composting facility within premises) with the approval of local body. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000
- 7. Applicant shall be responsible to take adequate precautionary measures as detailed in this consent.
- 8. The applicant/generator shall be responsible for safe and scientific collection, transportation, treatment and disposal of Bio-Medical Waste as per the provisions made under the Bio-Medical Waste (Management & Handling) Rules, 1998. Any activity as defined under BMW (M & H) Rules has to obtain a separate Authorization from Maharashtra Pollution Control Board.
- 9. For disinfections of waste water ultra violet radiation shall be used in place of chlorination.
- 10. E-Waste shall be disposed to authorized re processor.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under.

The daily water consumption for the following categories is as under:

(i) Domestic ... 1776.00 CMD

(ii) Water gets Polluted & Pollutants are Biodegradable ... 0.00 CMD

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic
(iv) Industrial Cooling, spraying ... 0.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under

Section 3 of the said Act.

5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

(i) The Applicant may install 8 Nos. of diesel generating sets (DG Sets), of capacity 500 KVA(4 Nos) and 300 KVA(4 Nos.) and shall be equipped with comprehensive control system as is warranted with reference to generations of emissions and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Standards for Emissions of Air Pollutants:

(i) SPM/TPM Not to exceed 150 mg/Nm3 (ii) SO2 (DG Set) Not to exceed 3.0 Kg/day

(ii) The following measures shall be taken:

- Adequate mitigation measures shall be taken to control emissions of SO2, NOx, SPM, and RSPM.
- b. Applicant shall achieve following Ambient Air Quality standards.

1.	SPM Not to Exceed (Annual Average)	140	μg/ m3
	Not to Exceed (24 hours)	200	μg/ m3
2.	SO2 Not to Exceed (Annual Average)	60	μg/ m3
	Not to Exceed (24 hours)	80	μg/ m3
3.	NOx Not to Exceed (Annual Average) Not to Exceed (24 hours)	60 80	µg/ m3 µg/ m3
4.	RSPM Not to Exceed (Annual Average)	60	μg/ m3
	Not to Exceed (24 hours)	100	μg/ m3

(iii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	IIOM
1	HSD	125.00	
		123.00	Ltrs/hr.

(iv) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	D.G. Set (4x500 KVA)	5.00
2	D.G. Set (4x300 KVA)	4.00

(v) Conditions for D.G. Set

- 1. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- 3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- 5. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- 6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- 7. D.G. Set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(vi) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.

(vii) Conditions for Utilities like Kitchen, Eating Places etc:

- 1. The kitchen shall be provided with exhaust system chimney with oil catcher connected to chimney through ducting.
- 2. The toilet shall be provided with exhaust system connected to chimney through ducting.
- 3. The air conditioner shall be vibration proof and the noise shall not exceed 68 dB (A).
- 4. The exhaust hot air from A.C. shall be attached to Chimney at least 5 mtrs. higher than the nearest tallest building through ducting and shall discharge into open air in such way that no nuisance is caused to neighbors.
- (viii) The Applicant shall take adequate measures for control of noise levels its own sources within the complex (residential cum Commercial) from noise to less than 55 dB(A) during day time and 45 dB(A) in respect of during the night time. Daytime is reckoned as between 6 a.m. to 10 p.m. and Nighttime is reckoned between 10 p.m. to 6 a.m.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall not generate any hazardous wastes.

- 7. The applicant shall take the proper remediation measures to ensure that the ground water and soil contamination is prevented, and follow due diligence at the construction stage.
- 8. The applicant shall comply with the conditions of Environmental Clearance granted by MoEF, GOI, vide No. 21-57/2006-IA.III dt. 17/05/2006.
- 9. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 10. This consent shall not be construed as exemption from obtaining necessary NOC from any other Government agencies as may deemed fit necessary.
- 12. This is issued with the approval of Consent Appraisal Committee of the Board in its meeting held on 15th December 2011.
- 13. The Capital investment of the project is Rs. 62000Lacs

(Milind Mhaiskar, _{IAS}) Member Secretary

To, Eon Kharadi Infrastructure Pvt. Ltd. Plot No. 1, S.No. 77, Kharadi Knowledge Park, Kharadi, Pune- 411014

Copy to:

- a. RO-Pune /SRO-Pune-II
- b. CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	620000	001355	13 Dec 2010	Saraswat Co-Op Bank
2	100	008516	21 Oct 2010	ICICI Bank
3	620000	002527	9 Nov 2011	Standard Chartered Bank